

# weber.floor epo thinner

DECORATIVE &  
TECHNICAL FLOORING

## THINNER FOR SOLVENT BASED EPOXY AND PRIMER

### PRODUCT

weber.floor epo thinner is a cautiously balanced combination of the proper solvents, providing a high solubility for weber.floor epo HB 50- L and weber.floor eposil – L.

It helps to give a longer open time for application. weber.floor epo thinner is a slow evaporating solvent and does not contain any glycol which may affect the drying time and the gloss of the cured epoxy film.

### SCOPE OF USE

- Used as thinner in all types of Epoxy paint and primer.

### ADVANTAGES

- Compatible with all epoxy products.
- Increase drying property
- Improve leveling properties on various surfaces
- Reduce viscosity without affecting clarity and gloss
- Cleans paint tools and equipment after use

### CHARACTERISTICS

Color	Clear
Specific gravity @ 25°C	0.88 ±0.05 kg/ltr
Flash point	25 °C
Viscosity	11 seconds Din cup #4

### INSTRUCTIONS FOR USE

#### PRODUCT PREPARATION

weber.floor epo thinner must be added to the mixture after 20 minutes during summer time at high temperatures and 30 minutes during winter time (+15°C), to ensure proper chemical reaction.

It should be mixed well till all the epoxy is dissolved and the desired viscosity is achieved.

weber.floor epo thinner cannot be used to reclaim a mixed coating that is near the end of its pot life.

### STORAGE

Two years after manufacturing date in its original packing non open and in dry cool area.



### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
4 L.	-	-	-	-	-	-	-
18 L.	-	-	-	-	-	-	-

### SAFETY PRECAUTIONS

Application should be done in a ventilated area away from any heat source. Wear protective gear for hands and eyes and avoid breathing of vapor. If mixed resin comes into contact with the skin, it should be promptly removed before hardening, followed by thoroughly washing the skin with soap and water. In case of heavy vapor inhalation, place affected person in an open-air area. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In all cases, seek medical attention. In case of fire, use CO2 foam to extinguish. Tightly seal containers when not in use, store them away from heat and carefully dispose empty ones.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

# weber.floor epo thinner

## NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:22

Edition: 09/15-A



SODAMCO Holding Tayar Center Bloc B 1st flr. De Gaulle str. P.O.Box 55-44 Sin el Fil Beirut Lebanon  
T +961 1 510863/4 M +961 3 380748 F +961 1 510862 [sodamco@sodamco.com](mailto:sodamco@sodamco.com) [www.sodamco-weber.com](http://www.sodamco-weber.com)

Lebanon . UAE . Syria . Qatar . KSA . Jordan . Kuwait . Oman