

Water based, water and oil repellent for tiles, stones and grout protection

PRODUCT

weberdry protect is a ready-to-use high performance solution, used to impact both water repellency and oil repellency to inorganic porous substrates such as tiles and stones without altering surface properties. It can be used as well for dirt repellent treatment. Made of Silane, siloxane and synthetic resins in diluted form, it penetrates the pores without creating a film on the surface, so the pores of the substrates remain open and consequently the water vapor diffusion is hardly affected. The product has very strong penetration properties due to low molecular weight. It should be used on air dry and absorbent surface.

SCOPE OF USE

weberdry protect is specially formulated to treat and protect the surface of tiles and stones as well as the external façades. **weber.stone proof** leaves a colorless appearance once applied on the surface. It can be applied on any type of tiles/stones, but the compatibility with the tile/stone should be tested on a small sample prior to application.

weberdry protect also helps in preventing the formation of mould and fungus on tile grouts.

CHARACTERISTICS

Appearance	Liquid yellowish
Density at 20 °C	Around 1
Base	water-based

INSTRUCTIONS FOR USE

PRODUCT PREPARATION

All surfaces should be sound, clean, dry, free from oil or dust. Tile adhesives and grouts should have completely dried and have acquired the recommended strength before application.

PRODUCT APPLICATION

weberdry protect is applied by brush, immersion or spray. In the latter case, the nozzle must be held near the surface to facilitate penetration. Tiles and stones need to be treated for saturation twice; the second layer must be applied before the first layer has totally dried (wet on wet). Best results are reached with a dry, absorbent surface. Always perform a test on a small sample before application.

RECOMMENDATION

It is strongly recommended to carry out a sample trial on site before any application on the tiles and stones.

CONSUMPTION

Consumption depends on the absorption of tiles or stones. It



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	5 Lit	-	-	-	5 Lit
-	-	-	20 Lit	-	-	-	20 Lit

ranges between 0.05 and 0.14 liter/m².

Always perform a test before application, to check the compatibility between **weberdry protect** and the tile/stone

STORAGE

1 year from manufacturing date, in non-open original packaging.

The containers must be protected from direct sunlight.

SAFETY PRECAUTIONS

It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting; in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics

are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:02