Weberep 321 PA Formerly "Conrep.321 PA"

Fair face concrete putty

PRODUCT

weberep 321 PA is a paste to be mixed with cement. The mixture produces a repair stucco used to level and fill the holes in concrete walls for a maximum thickness of 2 mm without cracking. It is used to achieve proper smoothing of concrete surface and to eliminate irregularities of concrete, bubbles, honey combs or cracks. weberep 321 PA can fill pin holes up to 5 mm wide.

ADMISSIBLE SUBSTRATES

Exterior and interior cementitious walls or ceilings.

- · Reinforced concrete surfaces
- · Under face of concrete slabs
- · Prefabricated concrete slabs
- · Traditional plaster

ASSOCIATED FINISHES

- · Plastic decorative coating, paints
- · Wall paper
- · Adhesive plastic finishes
- · Tiles fixed with a thin bed adhesive (Interior only) Surface treated with weberep 321 PA must not be recovered with products formulated with hydraulic binders.

CHARACTERISTICS

Appearance	White paste
Specific gravity	1.39
PH	8.8
Composition	Synthetic resins, mineral
	charges and admixtures
Wet mix life	< 1 hour
Temperature during	should be between + 5°C
application	and + 35°C

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrates must be clean, sound, dust free and free from all traces of oil and laitance. Traces of mould joints must be levelled

PRODUCT PREPARATION

Mix weberep 321 PA with equal quantity of cement until a homogeneous paste is obtained.

PRODUCT APPLICATION

Product is applied using a stainless steel trowel or stucco blade. Surfacing is obtained with one or several passes depending on requested finish. In hot weather, substrate should be moistened prior to application.



STORAGE

Can be store up to 6 months from manufacturing date in

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:P23

