

## A ready-to-use primer for the equalization and neutralization of the substrate

### PRODUCT

**weberpas PR SIL** is a ready-to-use Primer made of organic components, alkali resistant pigments and additives. **weberpas PR SIL** is used for internal and external walls in association with **weber.pas deco**, for the equalization and neutralization of the substrate before the application of **weberpas deco** and silicone-based wet renders. It is available in white.

### PROPERTIES

- Provides an even suction for the substrate
- Ready-to-use
- Easy to apply

### SUBSTRATES

Suitable substrates include masonry surfaces e.g. cement renders, lime plasters, concrete or cement board and gypsum plasterboard.

### INSTRUCTIONS FOR USE

#### SUBSTRATE PREPARATION

- Mineral and masonry substrates e.g. lime and cement plasters and cement renders must be completely dry and hard and free of shrinkage and movement.
- Remove mould oil from concrete surfaces
- For renovation the substrate should be free of old plaster and any loose material and peeling paint
- Repaired areas of the surface should have the same strength and hardness as the existing substrate

#### PRODUCT APPLICATION

- Remove the lid and mix manually
- Apply with a sponge roller or brush
- 1 coat only
- Cover the whole area
- Allow to dry for 24 hours

#### QUALITY ASSURANCE

**weberpas deco SIL** is quality controlled by weber management system.

#### SPECIAL RECOMMENDATIONS

For neutralisation of the substrate apply **weberpas PR SIL** 1 day before application of **weberpas deco**

- Ideal application temp 5°C to 35°C; protect from direct sun and rain during application
- Use only clean tools
- No water to be added



#### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
20 kg	20 kg	20 kg	20 kg	20 kg	20 kg	20 kg	20 kg

### CONSUMPTION

0.2 kg/m<sup>2</sup> - 100m<sup>2</sup>/20 kg pail

### STORAGE

12 months from production date in unopened buckets and kept in dry frost-free storage, under cover, off the ground and not in direct sunlight.

### QUALITY ASSURANCE

**weberpas PR SIL** is quality controlled by Weber Management System.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure,

use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG: 03