

Premium water base penetrating sealer

PRODUCT

weberstone proof is a premium water-based, no sheen, ready to use penetrating sealer, based on an innovative resin. It provide a maximum stain protection and can be used as a pre-grouting sealer for interior and exterior use. weber.stone proof penetrates the pores without blocking the moisture vapor transmission. It protects in less than 6h and achieves a full cure in 24 hours

SCOPE OF USE

weberstone proof is specially formulated to treat and protect all kind of surfaces: natural stone, unglazed tile, porcelain, concrete, bricks, and grout. It can be used as well for external facades. **weberstone proof** is a non-sheen and leave a natural look, colorless appearance once applied on the surface. It may also be used as a pre-grouting sealer.

CHARACTERISTICS

Appearance	Liquid
Color	Transparent
pH	8.7

INSTRUCTIONS FOR USE

PRODUCT PREPARATION

All surfaces should be sound, clean, dry, free from oil or dust. Tile adhesives and grouts should have completely dried and have acquired the recommended strength before application

PRODUCT APPLICATION

As water repellent:

weberstone proof is applied by brush, sponge or spray. Allow it to penetrate, wipe surface completely dry with a clean cloth after each application. Porous surfaces may require additional application, allow 30 minutes drying time between applications.

As pre-grout sealer/grout release:

Porous tile and stone can be stained by grout during installation. Sealing the tile before grouting will make grout removal much easier. Apply **weberstone proof** after tile has been bonded for a minimum of 24 hours, or apply to front face of tile before installation. Wait a minimum of 24 hours before grouting.

RECOMMENDATION

It is strongly recommended to carry out a sample trial on site before any application on the tiles and stones.

CONSUMPTION

0.05-0.14l/m²



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
5 Lit	-	-	5 Lit	-	-	-	5 Lit
20 Lit	-	-	20 Lit	-	-	-	20 Lit

This coverage is based on practical application by roller onto a smooth surface in optimum conditions. Factors like surface porosity, temperature, humidity, application method, affect highly the consumption ratio.

STORAGE

1 year from manufacturing date, in non-open original packaging.

The containers must be protected from direct sunlight.

SAFETY PRECAUTIONS

It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting; in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company

may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:02