

Slipping AID L

ADMIXTURES & CONCRETE
RELATED PRODUCTS

CLEANING AID FOR CEMENT BASED MATERIALS

PRODUCT

Slipping AID L is a special water based lubricant product being designed for direct application over steel surfaces that are mainly in contact with cement based materials.

PROPERTIES

Applying Slipping AID L on frequent basis will allow cement based materials to slide away easily with less vibration due to the formation of a thin colorless synthetic layer on the surface of steel. Consequently, steel will be protected from any undesired settlement of hardened cement based materials.

Slipping AID L will reduce the time of cleaning machines and is an environmental friendly.

SCOPE OF USE

Slipping AID L can be used on:

- Plant mixers
- Conveyers
- Hoppers
- Transit mixer
- Steel pallet in block factories.

CHARACTERISTICS

Appearance	Liquid
Color	Milky white
Freezing point	-3 °C approximate
Flash point	100 °C
Specific gravity	0.99 ± 0.05

INSTRUCTIONS FOR USE

Slipping AID L can be applied by spray, brush, roller or cloth.

It is recommended to agitate and stir the product before usage.

PACKAGING

Slipping AID L is supplied in:
1000 liter containers.
200 liter drum.
20 liter jerkin.

STORAGE

6 months if properly stored in original unopened package.

In case of frost, the product recovers its properties after progressive thawing and homogenizing by agitation.

HEALTH & SAFETY

In case of contact with skin or eyes, rinse thoroughly with water. If irritation persists, seek medical attention. If swallowed, do not induce vomiting and seek medical attention.

QUALITY STATEMENT

All our products are manufactured to comply with our internal QA/QC program and quality management system to ensure consistency and quality

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their applications are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that the Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

Edition: 06/13-A

