weberad cure Y 40 formerly "Cure Y 40"

Concrete curing compound

PRODUCT
weberad cure Y 40 is a water-based curing compound for newly placed concrete surfaces. It produces a moisture resistant membrane film on concrete surfaces to assure proper hydration of cement and reduce plastic shrinkage cracks.

SCOPE OF USE
For application to fresh concrete slabs or any other concrete surface to delay moisture loss.

CHARACTERISTICS	
Appearance	White liquid
Specific gravity	Approx.1
pH	7.5 ± 1
Color	Transparent when dried
Chloride free	

INSTRUCTIONS FOR USE
On fresh concrete or rendering as soon as the gloss of the surface becomes mat, and the bleeding stops, **weberad cure Y 40** is sprayed on the surface using a hand operated spray gun. **weberad cure Y 40** can be applied as well by roller or brush.
In case of over coating, it is recommended to check the adhesion & compatibility of the new coat and concrete surface treated with **weberad cure Y 40** before application.

APPLICABLE STANDARD
ASTM C 309 type 1 class B

CONSUMPTION
App. 8m² per liter.

PACKAGING
weberad cure Y 40 is supplied in:
4 lit, 20 lit, 25 lit, 200 lit and 1000 lit drums

STORAGE
Has a high storage stability: can be store up to 6 months from manufacturing date, in original and non open packaging. Storage temperature should not exceed +45°C over a long period.

HEALTH & SAFETY
In case of frost, the product recovers its properties after progressive thawing and homogenizing by agitation. In case of contact with skin or eyes, rinse thoroughly with water. If irritation persists, seek medical attention. If swallowed, do not induce vomiting and seek medical attention.

QUALITY STATEMENT
All our products are manufactured to comply with our internal QA/QC program and quality management system to ensure consistency and quality.

DISCLAIMER
While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE
The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.