

## Water-based shutter release agent

### PRODUCT

**weberad dem 22** is a water based release agent usable with all type of shuttering: steel, plastic, plywood (non-absorbant wood) or aluminum. It allows a clean, fast, and easy striking. It can be sprayed or applied with a cloth. Due to its white color, **weberad dem 22** is particularly recommended for architectural or fair faced concrete where no traces are allowed.

### SCOPE OF USE

- Concrete fabrication
- Formworks for gypsum
- Heavy prefabrication
- Formwork for prestressed concrete

### CHARACTERISTICS

Appearance	Liquid
Preparation	Ready to use
Color	Milky white
Freezing point	-3°C approximate
Flash point	≥ 100°C
Viscosity	60 CP at 20°C
Specific density	1 ± 0.1

### INSTRUCTIONS FOR USE

**weberad dem 22** is a ready to use release agent to be applied by spray, brush, roller, or cloth.

### YIELD

50 to 60 m<sup>2</sup>/L depending on the form used.

### PACKAGING

**weberad dem 22** is supplied in:  
4lit, 20lit, 25lit and 200 lit. drums.

### STORAGE

6 months from date of production if stored properly in original unopened packing.

### HEALTH & SAFETY

In case of frost, the product recovers its properties after progressive thawing and homogenizing by agitation. In case of contact with skin or eyes, rinse thoroughly with water. If irritation persists, seek medical attention. If swallowed, do not induce vomiting and seek medical attention.

### QUALITY STATEMENT

All our products are manufactured to comply with our internal QA/QC program and quality management system

to ensure consistency and quality.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:55