

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifierTrade name **weberdry PUR seal**

Safety data sheet no.: XXP014014

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating material**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SODAMCO S.A.L.

Main Road, Hosrayel (Jbeil), P.O. Box 65, Jbeil - Lebanon

T +961 9 790 920/1/2/3

F +961 9 790 924

ATTADAMUNIA for Construction Industries JSC

Tha'labah Al – Ameli Str.-P.O. Box 710844 Amman 11171 Jordan

T +962 6 420 0417

F +962 6 420 0418

SODAMCO Emirates Factory for Building Materials W.L.L.Industrial City of Abu Dhabi

ICAD 3, Plot No. 65 NR29-P.O. Box 96082-Abu-Dhabi -

T +971 2 550 9994

F +971 2 550 9449

SODAMCO S.A.L. - Dubai Branch

Al Quoz Industrial AreaP.O. Box 31320Dubai - U.A.E.

T +971 4 347 2640

F +971 4 340 3420

SODAMCO Qatar W.L.L.

Al Rayan Complex, Bloc B 5th Floor, Flat 17, Rayan Road, Al Musheireb, P.O. Box 22520, Doha – Qatar

T +974 4442 3816 / +974 4442 7651

F +974 4442 5149

SODAMCO Kuwait W.L.L.

Raja Abdulla Al Habbaj Office No. 3F/6, Bloc 7 P.O. Box 496 Salmiya 20005 Kuwait

T +965 2 571 6404 /+965 2 571 0397

F +965 2 571 2721

SODAMCO Muscat L.L.C.

Al Khuwair - Muscat - Sultanate of Oman-P.O. Box 1094 PC 133,

T +968 24 21 83 61

F +968 24 21 83 62

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Office Jeddah)

SODAMCO villa, Prince Mohammad Bin Abdul Aziz Street. P.O. Box 9927, Jeddah 21423 Kingdom of Saudi Arabia

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 1)

T +966 12 668 3295 +966 12 261 2722
F +966 12 668 1498

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Riyadh Office)
Salahuddin Al Ayoubi Street, Facing Military Airbase Al Bayt 52 Complex, Building 5 Office 1- P.O. Box
1042 Riyadh 11431-Kingdom of Saudi Arabia

T +966 11 473 8751

F +966 11 472 5339

1.4 Emergency telephone number:

UAE: +971 2 550 9994

Lebanon: +961 9790920

Jeddah: +966 126683295

Riyadh: +966 114738751

Qatar: +974 44423816

Jordan: +962 64200417

Kuwait: +965 25716404

Muscat: +968 24218361

Hours of operation: From 8 am to 6 pm

Monday to Friday in Lebanon

Sunday to Thursday in other countries

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 2)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS08

Signal word Danger

Hazard-determining components of labelling:

Xylene

m-tolylidene diisocyanate

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.**vPvB:** Does not contain vPvB substances.

EUG

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 3)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-20%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-xxxx	m-tolylidene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	0.1-1%
CAS: 64359-81-5 EINECS: 264-843-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one ⚠ Acute Tox. 1, H330; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; STOT SE 3, H335	<0.1%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice

Immediately remove any clothing soiled by the product.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

Seek immediate medical advice.

After swallowing

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 5)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 4)

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents** CO₂, powder or water spray. Fight larger fires with water spray.**For safety reasons unsuitable extinguishing agents** Water with full jet**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)**5.3 Advice for firefighters****Protective equipment:**

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation.

Wear protective clothing.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 6)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 5)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
DNELs
CAS: 1330-20-7 Xylene

Oral	Derived No Effect Level	1.6 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	180 mg/kgxday (worker systemic long term value)
		108 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	77 mg/m ³ (worker systemic long term value)
		289 mg/m ³ (worker systemic short term value)
		14.8 mg/m ³ (consumer systemic long term value)
		174 mg/m ³ (consumer systemic short term value)
		289 mg/m ³ (worker local short term value)
		174 mg/m ³ (consumer local short term value)

CAS: 26471-62-5 m-tolylidene diisocyanate

Inhalative	Derived No Effect Level	0.035 mg/m ³ (worker systemic long term value)
		0.14 mg/m ³ (worker systemic short term value)
		0.14 mg/m ³ (worker local short term value)
		0.035 mg/m ³ (worker local long term value)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 6)

Ingredients with biological limit values:
CAS: 1330-20-7 Xylene

BGW (Germany)	1.5 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Xylol
	2000 mg/L Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Methylhippur-(Tolur-)Säure (alle Isomere)
VLB (Spain)	1 g/g creatinina Muestra: orina Momento de Muestero: Final de la jornada laboral Indicador Biológico: Ácidos metilhipúricos
IBE (Italy)	1.5 g/g creatinina Campioni: urine Momento del prelievo: a fine turno Indicatore biologico: acido metilippurico
IBE (Portugal)	1.5 g/g creatinina Amostra: urina Momento da amostragem: Fim do turno Indicador biológico: Ácidos (o, m, p)-metilhipúricos
BNO (Finland)	5.0 mmol/l Altiste: virtsan Näytteenottoajankohta: Työvuoron päätyttyä Parametri: metyylihippuurihappo

CAS No.	Designation of material	%	Type	Value Unit
---------	-------------------------	---	------	------------

CAS: 1330-20-7 Xylene

IOELV (European Union)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
AGW (Germany)	Long-term value: 440 mg/m ³ , 100 ppm 2(II);DFG, EU, H
GV (Denmark)	Long-term value: 109 mg/m ³ , 25 ppm EH
LEP (Spain)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm vía dérmica, VLB, VLI
TWA (Italy)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm A4, IBE

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 7)

VL (Italy)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Pelle
VLE (Portugal)	Short-term value: 150 ppm Long-term value: 100 ppm A4;IBE; Irritação ocular, do TRS; afeção do SNC
OEL (Sweden)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm H
HTP (Finland)	Short-term value: 440 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm iho
CAS: 26471-62-5 m-tolylidene diisocyanate	
MAK (Germany)	vgl. Abschn.XII
OEL (Sweden)	Short-term value: 0.04 mg/m ³ , 0.005 ppm Long-term value: 0.014 mg/m ³ , 0.002 ppm C, M, S
HTP (Finland)	Short-term value: 0.035 mg/m ³ NCO

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls
Personal protective equipment:
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves.

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 8)

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection: Safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form:	Liquid
Colour:	Various colours
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	130 °C

Flash point: 27 °C (xylene)

Flammability (solid, gas): Not applicable.

Ignition temperature: 488 °C (xylene)

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	0.8 Vol.%
Upper:	Not determined.

Oxidising properties Not determined.

Vapour pressure: Not determined.

Density at 20 °C: 1.39-1.41 g/cm³

Bulk density: Not applicable.

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 9)

Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity: dynamic at 20 °C: kinematic:	>90 mPas Not determined.
Solvent separation test: Solvent content: EU-VOC (g/L)	Not determined 249.0 g/l
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition / Conditions to be avoided: Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid Keep away from sources of ignition. Protect from frost.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
Dermal	LD50	9,434 mg/kg (Calculation)	
Inhalative	LC50/4 h	35 mg/l (Calculation)	
CAS: 1330-20-7 Xylene			
Oral	LD50	4,300 mg/kg (Rat)	
Dermal	LD50	>1,700 mg/kg (Rabbit)	
Inhalative	LC50/4 h	21.7 mg/l (Rat)	
CAS: 26471-62-5 m-tolylidene diisocyanate			
Oral	LD50	>4,130 mg/kg (Rat)	

(Contd. on page 11)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 10)

Dermal	LD50	>9,400 mg/kg (Rabbit)
Inhalative	LC50/4 h	0.1 mg/l (Rat)

Primary irritant effect:
Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
--------------	-------------------------	--------	------------

CAS: 1330-20-7 Xylene

LC50/96h	2.6 mg/l (Fish)
----------	-----------------

CAS: 26471-62-5 m-tolylidene diisocyanate

LC50/96h	133 mg/l (Fish)
EC50/48h	12.5-18.3 mg/l (Daphnia magna)
EC50/96h	3.2-4.3 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential
CAS: 26471-62-5 m-tolylidene diisocyanate

EBAB	3.43 log Pow (Bioaccumulation)
------	--------------------------------

Behaviour in environmental systems:
12.4 Mobility in soil No further relevant information available.

Additional ecological information:
General notes: The product contains materials that are harmful to the environment.

12.5 Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

12.6 Other adverse effects No further relevant information available.

(Contd. of page 11)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Dispose of the product in accordance with national and local regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Contact manufacturer for recycling information.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

08 04 11*	adhesive and sealant sludges containing organic solvents or other hazardous substances
HP 3	Flammable
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Uncleaned packaging:
Recommendation:

Disposal must be made according to official regulations.
Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name
ADR
IMDG, IATA

1866 RESIN SOLUTION
RESIN SOLUTION

14.3 Transport hazard class(es)
ADR

Class
Label

3 (F1) Flammable liquids.
3

(Contd. on page 13)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 12)

IMDG, IATA


Class	3 Flammable liquids.
Label	3

14.4 Packing group	III
ADR, IMDG, IATA	

14.5 Environmental hazards:	Not applicable.
------------------------------------	-----------------

14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, S-E
Segregation groups	Acids
Stowage Category	A

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
--	-----------------

Transport/Additional information:

ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
Remarks:	Containers >450 L = UN 1866 - 3(F1) - RESIN SOLUTION, flammable

IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Remarks:	Containers >30 L = UN 1866 - 3(F1) - RESIN SOLUTION, flammable

IATA	
Remarks:	Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable

UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III
-------------------------------	--------------------------------

EUG

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 13)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Directive 2004/42/CE (VOC), cf. section 9

Labelling according to Regulation (EC) No 1272/2008 cf. section 2**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category** P5c FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

National regulations

Other regulations, limitations and prohibitive regulations

BG-Merkblätter: M 044 "Polyurethane production/Isocyanates"**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: R&D Department of Weber-Middle East

(Contd. on page 15)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.01.2019

Version number 3

Revision: 02.01.2019

Trade name weberdry PUR seal

(Contd. of page 14)

Contact:

Product Safety

T+97125509449

e-mail: DL-weber.productSafety-ME@Saint-gobain.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.