



Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weberdry PUR trans

Safety data sheet no.: XXP014676

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SODAMCO S.A.L

Main Road, Hosrayel (Jbeil), P.O. Box 65, Jbeil - Lebanon

T +961 9 790 920/1/2/3

F +961 9 790 924

ATTADAMUNIA for Construction Industries JSC

Tha'labah Al – Ameli Str.-P.O. Box 710844 Amman 11171 Jordan

T +962 6 420 0417

F +962 6 420 0418

SODAMCO Emirates Factory for Building Materials W.L.L.Industrial City of Abu Dhabi

ICAD 3, Plot No. 65 NR29-P.O. Box 96082-Abu-Dhabi -

T +971 2 550 9994

F +971 2 550 9449

SODAMCO S.A.L. - Dubai Branch

Al Quoz Industrial AreaP.O. Box 31320Dubai - U.A.E.

T +971 4 347 2640

F +971 4 340 3420

SODAMCO Qatar W.L.L.

Al Rayan Complex, Bloc B 5th Floor, Flat 17, Rayan Road, Al Musheireb, P.O. Box 22520, Doha – Qatar

T +974 4442 3816 / +974 4442 7651

F +974 4442 5149

SODAMCO Kuwait W.L.L.

Raja Abdulla Al Habbaj Office No. 3F/6, Bloc 7 P.O. Box 496 Salmiya 20005 Kuwait

T +965 2 571 6404 /+965 2 571 0397

F +965 2 571 2721

SODAMCO Muscat L.L.C.

Al Khuwair - Muscat - Sultanate of Oman-P.O. Box 1094 PC 133,

T +968 24 21 83 61

F +968 24 21 83 62

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Office Jeddah)

SODAMCO villa, Prince Mohammad Bin Abdul Aziz Street. P.O. Box 9927, Jeddah 21423 Kingdom of Saudi Arabia

(Contd. on page 2)



Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 1)

Page 2/15

T +966 12 668 3295 +966 12 261 2722

F +966 12 668 1498

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Riyadh Office)

Salahuddin Al Ayoubi Street, Facing Military Airbase Al Bayt 52 Complex, Building 5 Office 1- P.O. Box 1042 Riyadh 11431-Kingdom of Saudi Arabia

T +966 11 473 8751

F +966 11 472 5339

1.4 Emergency telephone number:

UAE:+971 2 550 9994 Lebanon:+9619790920 Jeddah:+966126683295 Riyadh:+966114738751 Qatar:+97444423816 Jordan: +96264200417 Kuwait:+96525716404 Muscat:+96824218361

Hours of operation: From 8 am to 6 pm

Monday to Friday in Lebanon

Sunday to Thursday in other countries

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 3)



Page 3/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 2)

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Xylene

1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type ethylbenzene

Distillates (petroleum), hydrotreated light

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

(Contd. on page 4)



Page 4/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 3)

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl) ethyl)carbamate Skin Sens. 1, H317	10-25%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24-xxxx	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type \$\ightarrow\$ Skin Sens. 1, H317; STOT SE 3, H335	5-10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5-10%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31-xxxx	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 3, H331; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1-1%
CAS: 540-84-1 EINECS: 208-759-1 Index number: 601-009-00-8	2,2,4-trimethylpentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	0.1-1%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take affected persons out into the fresh air.

Seek immediate medical advice

After inhalation

Supply fresh air and to be sure call for a doctor.

Seek medical treatment in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 5)



Page 5/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 4)

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

Protect unharmed eye.

Seek immediate medical advice.

After swallowing

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents CO2, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not

enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

(Contd. on page 6)



Page 6/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 5)

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special precautions are necessary if used correctly.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Prevent any seepage into the ground.

Provide ventilation for receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 133	0-20-7 Xylene	
Oral	Derived No Effect Level	1.6 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	180 mg/kgxday (worker systemic long term value)
		108 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	77 mg/m³ (worker systemic long term value)
		289 mg/m³ (worker systemic short term value)
		14.8 mg/m³ (consumer systemic long term value)

(Contd. on page 7)





Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

		(Contd. of page
		174 mg/m³ (consumer systemic short term value)
		289 mg/m³ (worker local short term value)
		174 mg/m³ (consumer local short term value)
CAS: 538	80-05-0 3-Isocyanatom isocyanurate ty	nethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer pe
Inhalative	Derived No Effect Level	0.58 mg/m³ (worker local short term value)
		0.29 mg/m³ (worker local long term value)
CAS: 108	-65-6 2-methoxy-1-meth	ylethyl acetate
Oral	Derived No Effect Level	36 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	796 mg/kgxday (worker systemic long term value)
		320 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	275 mg/m³ (worker systemic long term value)
		33 mg/m³ (consumer systemic long term value)
		550 mg/m³ (worker local short term value)
		33 mg/m³ (consumer local long term value)
CAS: 409	8-71-9 3-isocyanatomet	hyl-3,5,5-trimethylcyclohexyl isocyanate
Inhalative	Derived No Effect Level	0.0453 mg/m³ (worker local short term value)
		0.0453 mg/m³ (worker local long term value)
CAS No	o. Designation of mater	ial % Type Value Unit
	0-20-7 Xylene	
	_	rm value: 442 mg/m³, 100 ppm
•	Long-ter	m value: 221 mg/m³, 50 ppm
	Skin	
	-65-6 2-methoxy-1-meth	
IOELV (E		rm value: 550 mg/m³, 100 ppm
	Long-ter Skin	m value: 275 mg/m³, 50 ppm
	SKIII	

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 8)





Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 7)

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR Nitrile rubber, NBR

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection: Tightly sealed goggles **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and cher General Information	mical properties
Appearance:	
Form:	Liquid
Colour:	Transparent
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 162 °C
Flash point:	29 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	488 °C (xylene)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
	(Contd. on page 0)

(Contd. on page 9)





Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

		(Contd. of page
Explosion limits:		
Lower:	0.7 Vol %	
Upper:	7.5 Vol %	
Oxidising properties	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	1.01 g/cm³	
Bulk density:	Not applicable.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
Segregation coefficient (n-octanol/water) le	og	
Pow:	Not determined.	
Viscosity:		
dynamic at 20 °C:	>40 mPas	
kinematic:	Not determined.	
Solvent separation test:	Not determined	
Solvent content:		
EU-VOC (g/L)	330.0 g/l	
9.2 Other information	No further relevant information availa	able.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / Conditions to be avoided: Stable at environment temperature.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compone	nts	Type	Value	Species	
Dermal	LD50	4,545 mg/kg (Calcւ	ılation)		

(Contd. on page 10)





Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

		(Contd. of page 9)
Inhalative	LC50/4 h	40 mg/l (Calculation)
CAS: 1330	0-20-7 Xyl	ene
Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	>1,700 mg/kg (Rabbit)
Inhalative	LC50/4 h	21.7 mg/l (Rat)
CAS: 5388		Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer,
	is	ocyanurate type
Oral	LD50	14,000 mg/kg (Rat)
Inhalative	LC50/4 h	>5 mg/l (Rat)
CAS: 108-	-65-6 2-me	thoxy-1-methylethyl acetate
Oral	LD50	>6,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
CAS: 4098	8-71-9 3-is	ocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
Oral	LD50	4,814 mg/kg (Rat)
Dermal	LD50	7,000 mg/kg (Rat)
Inhalative	LC50/4 h	>31 mg/l (Rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test Effective concentration M	letnod Assessment
--	-------------------

EC50/48h >500 mg/l (Daphnia magna)

(Contd. on page 11)





Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 10)

CAS: 1330	0-20-7 Xylene
LC50/96h	2.6 mg/l (Fish)
CAS: 5388	80-05-0 3-lsocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate homopolymer, isocyanurate type
LC50/96h	>1.5 mg/l (Fish)
EC50/48h	3.36 mg/l (Daphnia magna)
EC50/72h	3.6 mg/l (Algae)
CAS: 108-	65-6 2-methoxy-1-methylethyl acetate
LC50/96h	161 mg/l (Pimephales promelas (Minnow))
	140 mg/l (Fish)
EC50/48h	>500 mg/l (dap)
CAS: 4098	3-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
LC50/96h	208 mg/l (Fish)
EC50/72h	4.8 mg/l (Daphnia magna)
	70 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

EBAB 4.7 log Pow (Bioaccumulation)

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Dispose of the product in accordance with national and local regulations.

Must not be disposed together with household garbage. Do not

allow product to reach sewage system.

European	waste catalogue
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 6	Acute Toxicity

(Contd. on page 12)





Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 11)

HP 13 Sensitising

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A

(Contd. on page 13)



according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 12)

Page 13/15

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3
Tunnel restriction code D/E

Remarks: Not subject to ADR Class 3 if containers < 450L

according to ADR 2.2.3.1.5.

Containers >450 L = UN 1866 - 3(F1) - RESIN

SOLUTION, flammable

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Remarks: Not subject to IMDG Class 3 if containers < 30L

according to IMDG 2.3.2.5.

Containers > 30 L = UN 1866 - 3(F1) - RESIN

SOLUTION, flammable

IATA

Remarks: Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN

SOLUTION, flammable

UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Directive 2004/42/CE (VOC), cf. section 9

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 14)



Page 14/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 13)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: R&D Department of Weber-Middle East

Contact:

Product Safety T+97125509449

e-mail: DL-weber.productSafety-ME@Saint-gobain.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

(Contd. on page 15)



Page 15/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.01.2019 Version number 1 Revision: 02.01.2019

Trade name weberdry PUR trans

(Contd. of page 14)

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.