

## Mono-componenty acrylic-based flexible waterproof.coating

### PRODUCT

**weberdry 210 AFC** is elasticized, acrylic, water-based, Waterproof membrane. **weberdry 210 AFC** is designed for under tile use in demanding internal & external waterproofing applications. Properly applied, **weberdry 210 AFC** cures to form a durable, elastic, seamless odorless and impervious membrane that will not re-emulsify once it has fully cured even if continually immersed in water. It has a good resistance to alkalis, salt solutions & diluted acids, non hazardous composition with excellent strength & flexible characteristics.

### SCOPE OF USE

**weberdry 210 AFC** has been specifically designed for the long term waterproofing of wet areas inc. shower, bathrooms, laundries, exterior decks, terraces and balconies. It can be used to waterproof exposed roofs; however water ponding should not be allowed for durations exceeding 48 hours.

### CHARACTERISTICS

Paste appearance	Pink
Paste density	1.560
Ideal application temperature	5 to 35°C
Pull off Strength @ 14 days ( ASTM D4541)	1.2 MPa

### INSTRUCTIONS FOR USE

#### PREPARATION OF THE SUBSTRATE

Substrates should be dry, smooth, sound and free from oil, grease, waxes, dust, laitance and all loose matter. Any surface defects should be repaired prior to application of membrane.

#### PRODUCT APPLICATION

Apply the 1st layer of **weberdry 210 AFC** with sufficient thickness to plug pores, cracks, and holes. Allow to dry and apply the second layer.

All corners, cracks or construction joints should receive 20 cm wide Fiber Mesh reinforcement between the 1st and 2nd layer.

Wherever tiling on **weberdry 210 AFC** is required, it is recommended that the tiling must start 24 hours after the application of **weberdry 210 AFC**.

### COVERAGE

0.260 kg/m<sup>2</sup> over smooth substrate.



### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
15 Kg	15 Kg	15 Kg	15 Kg	15 Kg	15 Kg	15 Kg	15 Kg

### STORAGE

Can be stored up to 6 months from manufacturing date, in original packaging, non open, protected from humidity, hot or freezing temperature.

### SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure,

use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:27