# High wear, Anti-slip controlled sizing natural sand

#### **PRODUCT**

weberfloor Sil S is a closely controlled sizing Natural sand generally used as an anti-slip finish to roughen the substrate in several applications such as flooring systems, liquid coatings systems and tile fixing to make the surface slip and wear resistant

#### **SCOPE OF USE**

- To roughen the substrate prior to the self Levelling compounds or smoothing compounds application over ceramic tiles.
- As anti-slip for the epoxy and polyurethane Floor coatings system application.
- Prior to tile adhesive applications over polyurethane liquid membranes.
- As an intermediate coat between the self Leveling or smoothing and the vapor barrier compounds.
- · To increase the epoxy resin fairing coat application thickness.

CHARACTERISTICS	
Form	Natural sand
Color	off white
Bulk Density	1.5 ± 0.1
available grades	0.1-0.3 mm
	0.3-0.8 mm
	0.5-1.0 mm
SiO2	>98%
grain shape	rounded shape
solubility in water	not soluble
Hardness	7 mohs

#### **STORAGE**

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

### **SAFETY PRECAUTIONS**

Non Hazardous material but avoid prolonged breathing of dust. When in contact with eyes, can cause irritation. Immediately flush eyes with plenty of water for at least 15 minutes. Please check the MSDS for further details.

## DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company



may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

#### NOTE

The information included on this Technical Data Sheet is the sole property of weber. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

