

Primer for polysulphide sealant

PRODUCT

weber seal prime PS is a single component primer especially developed to enhance the bonding of polysulphide sealant with the porous substrates such as cement , concrete , wood , stones etc.

SCOPE OF USE

- Primer for polysulphide sealant.
- Enhance the bonding of polysulphide sealant with the substrate.

CHARACTERISTICS

Appearance	Pale yellow to light brown
Composition	Single component moisture sensitive liquid
Specific gravity	1.00 ± 0.05
Viscosity	12-18sec. (on Ford Cup B4)
Interval time between coats	15-20min.
Sealant application time	30 min. after primer application
Number of coats required	2

INSTRUCTIONS FOR USE

weber seal prime PS can be applied by brush. All surfaces have to be clean, thoroughly dry and free of oil or any loose particles remaining.

CONSUMPTION

4.6m² - 5.6m²/lit/coat (depending on the surface porosity).

STORAGE

12 months from the manufacturing date in the original unopened containers, stored in a cool and dry place..

SAFETY PRECAUTIONS

Application should be done in a ventilated area away from any heat source. Wear protective gear for hands and eyes and avoid breathing of vapor. If mixed resin comes into contact with the skin, it should be promptly removed before hardening, followed by thoroughly washing the skin with soap and water. In case of heavy vapor inhalation, place affected person in an open-air area. In case of contact with eyes, wash thoroughly with clean water.

If swallowed, do not induce vomiting. In all cases, seek medical attention. In case of fire, use CO2 foam to extinguish. Tightly seal containers when not in use, store them away from heat and carefully dispose empty ones.



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
1 Lit	1 Lit	1 Lit	1 Lit	1 Lit	1 Lit	1 Lit	1 Lit

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

PG:29