

Air-entraining agent in powder form

PRODUCT

Admix GEL P is powder air-entraining agent of modified resins. It is specifically designed for concrete exposed to freeze/thaw conditions.

PROPERTIES

- **Admix GEL P** can entrain 2% to 6% air volume in the concrete. It produces an air-void system of microscopic air bubbles that remains stable in the plastic concrete enabling the improvement of frost durability of the concrete.
- Less mixing water can be used per cubic meter of concrete and overall workability is improved.
- Minimizes bleeding and segregation.

SCOPE OF USE

- Ready-mixed concrete
- Structural concrete
- Mass concrete construction
- Paving concrete
- Exterior concrete work exposed to freeze/thaw conditions

CHARACTERISTICS

Appearance	White powder
Specific gravity	1.17 ± 0.01

INSTRUCTIONS FOR USE

Admix GEL P is typically introduced during concrete mixing. The amount to be used will vary depending on type of cement, fineness of sand, temperature, mix design, etc. Concrete mixtures must be tested regularly to confirm that the proper air content is achieved.

For adequate resistance to freezing and thawing, the volume of entrained air should be about 4% to 6%, depending on the maximum size of aggregates.

Above these values, a reduction in mechanical strength can be noted.

DOSAGE

A dosage of 0.15 kg per 100 kg of cement is recommended as a starting point.

The required dosage depends on the concrete mixture and mixing conditions and can range between 0.15 kg and 1 kg / 100kg of the cement mass.

PACKAGING

Admix GEL P is packed in 1 kg plastic bag.
7 kg bag only for UAE & Oman.

SAFETY PRECAUTIONS

The product contains very fine powder which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning thoroughly with soap and water. In case of contact with eyes, wash thoroughly with clean water and seek medical attention. If swallowed, do not induce vomiting and seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

**Available only in MENA