

## Polyester stone adhesive

### PRODUCT

**webercol marble** is a two component marble and natural stone adhesive based on polyester resin. Used for gluing, repairing and filling up porous surfaces of the marble, travertine, natural stones, ceramic, brick and similar materials. Can be used both vertical and horizontal application.

### ADVANTAGES

- Rapid cure time
- Easy to apply
- Excellent brightness after the use of grinding machines.
- Very good adhesion on natural stones even at higher temperatures
- No color change, cracking or shrinkage during hardening period

### SCOPE OF USE

It is suitable for gluing concrete surfaces and natural stones like marble, granite, travertine.

### CHARACTERISTICS

|                         |                                |
|-------------------------|--------------------------------|
| Color                   | Bone white                     |
| Density                 | 1,94 ± 0,02 gr/cm <sup>3</sup> |
| Mix ratio               | 1-2 %                          |
| Application temperature | +5 °C to +40 °C                |
| Min Cure time           | 3 – 6 min                      |
| Max heat resistance     | 100 °C                         |

### INSTRUCTIONS FOR USE

The surface must be clean, dry and free from dust and grease. Porosity and roughness of the surface favor best adhesion.

Part A is mixed with Part B at the rate of 1-2% until a homogenous mixture is obtained then applied on the surface.

The hardener rate depends on temperature and the quantity of Part A.

An excess of hardener increases the hardening speed but weakens the adhesive seal.

The spatula is the tool required for application.

### STORAGE

Store in airtight original containers at temperatures not exceeding 30 °C. Keep away from direct sunlight and source of heat. If stored properly, shelf life is 2 years.

### SAFETY PRECAUTIONS

Irritating to eyes and skin. Avoid contacting eyes. Do not



### PACKAGING

| Leb | Syria | Jordan | UAE | Qatar | Kuwait | KSA | Oman |
|-----|-------|--------|-----|-------|--------|-----|------|
| -   | -     | 25 kg  | -   | -     | -      | -   | -    |
| -   | -     | 3 kg   | -   | -     | -      | -   | -    |

inhale. If eyes contact occurs, immediately flush eyes with plenty of water and consult a doctor. Use only in well-ventilated areas. Keep away from fire. Keep locked up and away from children. Wear gloves during application.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

\*\*Available only in MENA