



# Construction

## Residential

### weberad cure WT

Curing compound for fresh concrete surfaces

1



20 kg

### weberdry 110 FX

Flexible high-performance cement-based waterproof coating

2



15 Kg

### weberdry 150 BLC

Fast setting cementitious plugging mortar

3



1 or 5 or 20 Kg

### weberanc 405 BFX

Pure epoxy anchoring resin in cartridge

4



400 ml

### weberdry 132 WB

Water based surface water repellent

5



5 or 25 Kg

### weberep 370 PF

Two-component cement based corrosion protection and bonding agent

6



4 Kg

### weberdry 130 PR

Cement based waterproof coating

7



32.5 kg

### weberep 332 FFR

Non shrink thixotropic fine repair mortar with fiber

8



25 Kg

### weberep 360 FFR

Pre-mixed cementitious paste for fair face repair

9



20 Kg

### webertec 311 MC

Non-shrink fluid micro concrete

10



39 kg

1	ad cure WT	Curing concrete in hot weather
2	dry 110 FX	Waterproofing a retaining wall
3	dry 150 BLC	Sealing a water leak
4	anc 405 BFX	Anchoring reinforcement bars
5	dry 132 WB	waterproofing a façade
6	ep 370 PF	Protecting steel reinforcement
7	dry 130 PR	Waterproofing a basement or an elevator pit
8	ep 332 FR	Structural concrete repair with smooth finishing
9	ep 360 FFR	Filling pinholes and hairline cracks
10	tec 311 MC	Repair by grouting above 10 cm thick
11	ep 331 TX	Concrete repair with exposed steel
12	tec 301	Repair by grouting up to 10 cm thick

- High curing efficiency
- White at application
- Sprayable

- Excellent crack accommodation
- Resists high hydrostatic positive and negative pressures
- Approved for contact with potable water

- Stops water leaks instantly
- Fast setting plugging mortar
- High pressure resistant

- High bond strength with High load resistance
- Used in dry and wet concrete
- F 120 fire resistant

- Easy to apply
- Stainless surface waterproofing
- Colorless

- Highly corrosion inhibiting
- Improves adhesion of overcoating
- Impermeable to water

- Resistant to positive and negative water pressure
- Non toxic
- Approved for contact with potable water

- Non-shrinking
- Fine repairs
- Good resistance to sea water and to high-sulfate wate

- Smooth finish
- Applicable over large areas
- Available in white and light grey

- Non-shrinking
- Very High strength
- Low water absorption

