

MATERIAL SAFETY DATA SHEET

weber seal PS 2000 JF Formerly "Jointseal.PS 2000 JF"- Accelerator

EDITION: March 2018

1. IDENTIFICATION

Product Name: weber seal PS 2000 JF - Accelerator

Description: Two part cold applied elastomeric polysulfide jet fuel resistant joint sealant for concrete pavements.

SUPPLIER / MANUFACTURER:

SODAMCO Qatar: Rayan Road Al Musheireb, P.O. Box 22520- Doha-QATAR

SODAMCO UAE: Industrial city, ICAD III, P.O. Box 96082 Abu Dhabi – UAE

Al Quoz industrial area, P.O. Box 31320 Dubai - UAE

SODAMCO KSA: Bin Abdul Aziz Str., P.O. Box 222 –Jeddah 21411- KSA

Salahuddin Al Ayoubi Str. Bldg No.5 Riyadh - KSA

SODAMCO Jordan:Tha'labah al ameli Str., P.O. Box 710844 Amman 11171- JORDAN

SODAMCO Lebanon: Nahr el-Mot - Beirut- LEBANON

SODAMCO S.A.L: Main Road, Hosrayel (jbeil), P.O. Box 11-9666- Beirut-LEBANON

SODAMCO Kuwait: P.O. Box 496 Salmiya 20005 State of Kuwait

SODAMCO Syria: Kafarsouseh – Damascus Syria

SODAMCO Muscat: Al Khuwair, P.O.Box 1094 PC 133, CPO, Muscat – OMAN

INFORMATION:

SODAMCO Qatar: 00 974 4 4423816 –SODAMCO UAE: 00971 4 347 2640 - 00971 2 550 9994

SODAMCO KSA: 00966 12 668 3295 / 966 11 473 8751 – SODAMCO Jordan: 00962 6 4200417 –

SODAMCO Lebanon: 00961 70 258 393 – SODAMCO S.AL: 00961 9 790 920 – SODAMCO Syria:

00963 11 214 5548 – SODAMCO Kuwait: 00965 2 571 6404 – SODAMCO Muscat : 00968 24 21 83

61

2. COMPOSITION / INGREDIENTS

Hazardous Ingredient(s)	CAS No.	%
Manganese dioxide	1313-13-9	40-60
Chlorinated paraffin	85535-84-8	20-30

3. HAZARDS IDENTIFICATION

Inhalation of vapors or mists may cause severe irritation to nose, throat, and lungs. Prolonged and repeated inhalation of vapors/mists may cause headaches and may cause severe damage of the mouth and stomach.

Irritating to eyes and skin.

May cause sensitization by skin contact

Ingestion May cause irritation of the mouth, throat and gastrointestinal tract.

Environmentally hazardous

4. FIRST AID MEASURES

MATERIAL SAFETY DATA SHEET

weber seal PS 2000 JF Formerly "Jointseal.PS 2000 JF"- Accelerator

EDITION: March 2018

Eyes Immediately flush with plenty of water for at least 15 minutes. Keep eyelids open. Consult a physician immediately. Remove contact lenses before washing eyes. Discard the lenses.
Skin Wash material off with plenty of soap and water. Repeat soap and water washing several times to ensure removal from skin folds and beneath fingernails and toenails. If redness, itching or burning develops, consult a physician.

Inhalation Remove person to fresh air. If not breathing, give artificial respiration. If breathing is labored, give oxygen.

Get medical help immediately. Do not give any food or liquids to an unconscious person.

Ingestion Give 1 or 2 glasses of water to drink. If gastrointestinal symptoms develop, get medical help immediately. (Do not give anything by mouth to an unconscious person).

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: In case of fire use powder foam, or water fog-Do not use water Jets.

Special fire fighting procedures: Wear protective equipment such as fire resistant coveralls, respirators, etc.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment. Keep people away from the area. Work from the windward side. **Environmental precautions:** Do not flush into surface water or sanitary sewer system.

Methods for cleaning up: Dike area of spill and collect the spillage in a suitable container. If possible, solidify the Component with the Base-Component and solidify the waste. Store the waste in a dry, cool location before disposal.

7. HANDLING & STORAGE

Store in a cool, dry location. Avoid any contact with oxidizers and acids.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Wear MSHA/NIOSH approved organic vapor or charcoal filtered cartridge respirator or positive pressure supplied air respirator with full face piece or an air-supplied hood.

VENTILATION: local and or mechanical exhaust.

PROTECTIVE GLOVES: Nitrile, neoprene, and butyl rubber gloves.

EYE PROTECTION: Chemical tight goggles, full face shield in addition if splashing is possible.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WORK/HYGIENIC PRACTICES: Provide eye station. Provide showers. Wash before eating, drinking or smoking. Do not smoke around the uncured material or open containers.

9. PHYSICAL AND CHEMICAL PROPERTIES

State	Liquid
Colour	Brown black
Odour:	Organic
Flash point:	>150°C
Auto flammability	None
Specific gravity:	1.8

MATERIAL SAFETY DATA SHEET

weber seal PS 2000 JF Formerly "Jointseal.PS 2000 JF"- Accelerator

EDITION: March 2018

Water solubility: Insoluble

10. STABILITY AND REACTIVITY

Under normal conditions the product is stable. Avoid open flame and sparks.

Hazardous Decomposition or Byproducts: Carbon Monoxide. Irritant fumes

Materials to avoid: Strong acids, alkalis and oxidizing agents

Hazardous Polymerization will not occur

11. TOXICOLOGICAL PROPERTIES

No available data for this section.

12. DISPOSAL CONSIDERATIONS

Dispose in accordance to federal, state, and local regulations.

13. TRANSPORT INFORMATION

Non-regulated

14. OTHER INFORMATION

Uses: No other information

This safety data sheet should be used in conjunction with the product's technical data sheet. It does not replace it. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligations, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his responsibility.