

MATERIAL SAFETY DATA SHEET

weber seal PS 2000 JF Formerly "Jointseal.PS 2000 JF"- Base

EDITION: March 2018

1. IDENTIFICATION

Product Name: weber seal PS 2000 JF - Base

Description: Two part cold applied elastomeric polysulfide jet fuel resistant joint sealant for concrete pavements.

SUPPLIER / MANUFACTURER:

SODAMCO Qatar: Rayan Road Al Musheireb, P.O. Box 22520- Doha-QATAR

SODAMCO UAE: Industrial city, ICAD III, P.O. Box 96082 Abu Dhabi – UAE

Al Quoz industrial area, P.O. Box 31320 Dubai - UAE

SODAMCO KSA: Bin Abdul Aziz Str., P.O. Box 222 –Jeddah 21411- KSA

Salahuddin Al Ayoubi Str. Bldg No.5 Riyadh - KSA

SODAMCO Jordan:Tha'labah al ameli Str., P.O. Box 710844 Amman 11171- JORDAN

SODAMCO Lebanon: Nahr el-Mot - Beirut- LEBANON

SODAMCO S.A.L: Main Road, Hosrayel (jbeil), P.O. Box 11-9666- Beirut-LEBANON

SODAMCO Kuwait: P.O. Box 496 Salmiya 20005 State of Kuwait

SODAMCO Syria: Kafarsouseh – Damascus Syria

SODAMCO Muscat: Al Khuwair, P.O.Box 1094 PC 133, CPO, Muscat – OMAN

INFORMATION:

SODAMCO Qatar: 00 974 4 4423816 –SODAMCO UAE: 00971 4 347 2640 - 00971 2 550 9994

SODAMCO KSA: 00966 12 668 3295 / 966 11 473 8751 – SODAMCO Jordan: 00962 6 4200417 –

SODAMCO Lebanon: 00961 70 258 393 – SODAMCO S.AL: 00961 9 790 920 – SODAMCO Syria:

00963 11 214 5548 – SODAMCO Kuwait: 00965 2 571 6404 – SODAMCO Muscat : 00968 24 21 83

61

2. COMPOSITION / INGREDIENTS

Chemical Family

Hazardous ingredient(s)	CAS No.	%
Polysulfide resin	68611-50-7	20-30
Chlorinated paraffin	85535-84-8	40-50

3. HAZARDS IDENTIFICATION

Inhalation of vapors or mist may cause irritation to nose , throat and lungs.

May cause headache on prolonged and repeated inhalation.

May cause sensitization by skin contact.

Eye contact may cause severe damage including blindness. May also result in tearing, redness and possible burns.

Ingestion may result to irritation of mouth, throat and stomach.

4. FIRST AID MEASURES

MATERIAL SAFETY DATA SHEET

weber seal PS 2000 JF Formerly "Jointseal.PS 2000 JF"- Base

EDITION: March 2018

Inhalation: Remove person to fresh air. If not breathing, give artificial respiration. If breathing is labored, give oxygen.

Get medical help immediately. Do not give any food or liquids to an unconscious person.

Skin contact: Wash material off with plenty of soap and water. If redness, itching or burning develops, consult a physician.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Keep eyelids open. Consult a physician immediately.

Ingestion: Give 1 or 2 glasses of water to drink. If gastrointestinal symptoms develop, get medical help immediately. (Do not give anything by mouth to an unconscious person).

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: In case of fire use Carbon dioxide, powder, foam fog-Do not use water Jets..

Special fire fighting procedures: Wear protective equipment such as fire resistant coveralls, respirators, etc.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment. Keep people away from the area.

Work from the windward side. Environmental precautions: Do not flush into surface water or sanitary sewer system.

Methods for cleaning up: Dike area of spill and collect the spillage in a suitable container. If possible, solidify the Component with the accelerator Component.

7. HANDLING & STORAGE

Store in a cool, dry location. Avoid any contact with oxidizers and acids.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not required under normal condition. However if required wear MSHA/NIOSH approved organic vapor or charcoal filtered cartridge respirator.

VENTILATION: local and or mechanical exhaust.

PROTECTIVE GLOVES: Nitrile, neoprene, and butyl rubber gloves.

EYE PROTECTION: Chemical tight goggles or safety glasses, full face-shield in addition if splashing is possible.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WORK/HYGIENIC PRACTICES: Wear coveralls and/or aprons to avoid body contact. Provide eye wash station and showers on the job site in case of eye or skin contact. Wash before eating, drinking and smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Off-white

Odour: Faint

Flash point: >150 °C

Auto flammability: None

Specific gravity: 1.6

Water solubility: insoluble

MATERIAL SAFETY DATA SHEET

weber seal PS 2000 JF Formerly "Jointseal.PS 2000 JF"- Base

EDITION: March 2018

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

11. TOXICOLOGICAL PROPERTIES

No available data for this section.

12. DISPOSAL CONSIDERATIONS

Dispose in accordance to federal, state, and local regulations.

13. TRANSPORT INFORMATION

Non-regulated

14. OTHER INFORMATION

Uses: No other information

This safety data sheet should be used in conjunction with the product's technical data sheet. It does not replace it. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligations, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his responsibility.