

Admix SEC L

ADMIXTURES & CONCRETE
RELATED PRODUCTS

WATER-REDUCER PLASTICIZER / WATERPROOFING ADMIXTURE

PRODUCT

Admix SEC L is a water-reducer plasticizer and waterproofing agent for concrete.

Added to the mixing water in concrete, it deflocculates the cement particles and reduces the surface water tension, leading to reduction of the mixing water, greater workability, and complete hydration of cement.

Admix SEC L is chloride-free and soluble in water.

PROPERTIES

- Admix SEC L allows reduction of the Water / Cement ratio by 8 to 12%. Compare to a reference specimen, for the same workability, it improves the compactness of fresh concrete and increases slightly the mechanical strength
- Admix SEC L gives to concrete lasting water tightness against capillary bleeding and pressurized water
- Admix SEC L reduces shrinkage
- It prevents sweating, segregation and lost of laitance
- It gets a better casing of steel

SCOPE OF USE

Recommended for use in structural concrete such as: Foundation concrete, tanks, swimming pools, dams, river locks, road works...

CHARACTERISTICS

Appearance	Brown Liquid
Specific gravity	1.06 ± 0.03

APPLICABLE STANDARD

Classification : ASTM C 494 Type A & D

INSTRUCTIONS FOR USE

Admix SEC L is to be added to the mixing water. The total concrete mixing water should be reduced by 5% to 10% before the introduction of Admix SEC L. During the mixing, adjust the consistency of the mixture by adding small quantities of water, until the required plasticity is reached.

DOSAGE RATES

Recommended dosage for waterproofing effect: 0.5 kg per 100 kg cement.

If more plasticity is required, the dosage may be increased up to 1.5 kg per 100 kg of cement.

RETARDING EFFECT

At dosage rate higher than 1.5% of cement mass, the delay for the beginning of setting of concrete can be increased, depending on the quantity of cement used.

PACKAGING

Admix SEC L is supplied in:

Bulk

200 and 25 lit. drums

STORAGE

Admix SEC L can be stored up to 1 year from manufacturing date under cover, out of direct sunlight and protected from extreme temperatures.

HEALTH & SAFETY

In case of frost, the product recovers its properties after progressive thawing and homogenizing by agitation. In case of contact with skin or eyes, rinse thoroughly with water. If irritation persists, seek medical attention. If swallowed, do not induce vomiting and seek medical attention.

QUALITY STATEMENT

All our products are manufactured to comply with our internal QA/QC program and quality management system to ensure consistency and quality.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

Edition: 09/08-A

**Available only in MENA



SODAMCO Holding Tayar Center Bloc B 1st flr. De Gaulle str. P.O.Box 55-44 Sin el Fil Beirut Lebanon
T +961 1 510863/4 M +961 3 380748 F +961 1 510862 sodamco@sodamco.com www.sodamco.com

Lebanon . UAE . Syria . Qatar . KSA . Jordan . Kuwait . Oman