

## Primer for gypsum board substrates under 2K cementitious waterproofing

### PRODUCT

**weberdry prime G** is specially formulated for use as a primer on gypsum boards prior to the application of a 2k cementitious waterproofing products to improve the adhesion.

### SCOPE OF USE

Primer for cementitious waterproofing applications on gypsum boards.

### CHARACTERISTICS

Density	Approx 1 kg / lit
Color	Milky white
Drying time	1/2 to 2 hours depending on Application rate and climatic Conditions
Service Temperature	0 to +70°C

### INSTRUCTIONS FOR USE

#### PREPARATION OF THE SUBSTRATE

The substrate must be clean, dry and free from grease, oil, dust or any contamination that may prevent adhesion.

#### PRODUCT APPLICATION

Shake container well before use. Apply the primer evenly, using a brush, roller or small broom, over the gypsum board substrate and leave to dry to a clear thin film before applying the 2k cementitious waterproofing. It is important that the primer fill the entire surface to ensure a solid bond of the cementitious waterproofing. Clean tools with water when wet.

#### COVERAGE

100 to 200 ml/m<sup>2</sup>.

#### STORAGE

**weberdry prime G** can be stored up to 6 months after manufacturing date, in original packaging, protected from direct sun light in a covered area.

#### SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

#### DISCLAIMER

While the company guarantees its products against defective materials, all recommendations concerning the use and application of these products are made without guarantee



### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
5 Lit	5 Lit	5 Lit	5 Lit	5 Lit	5 Lit	5 Lit	5 Lit
20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit

since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.