

## Solvent based bitumen primer

### PRODUCT

**weberdry prime SB** is solvent-based primer, used for the preparation of surface to be waterproofed, with the aim of improving adherence of the waterproofing bituminous membranes to the substrate. The product can be applied on the majority of traditional surface in building.

### PROPERTIES

- Excellent adherence to all traditional substrate in building
- High penetration capacity on porous surface
- Excellent coverage rate
- Fast- drying
- Strengthens surfaces, eliminating loose dust



### PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	20 Lit	-	-	-	20 Lit
-	-	-	200 Lit	-	-	-	200 Lit

CHARACTERISTICS	Type 1	Type 2
Appearance	Black colored liquid	Black colored liquid
Density at 25°C	0.90 ± 0.05 g/ cm <sup>3</sup>	0.91 ± 0.5 g/cc
Saybolt Furol Viscosity 25°C	25-75 S	120-800 sec
Flash point	Min. 38°C	45-50°C
Water solubility	Insoluble	Insoluble
Benzene solubility	Soluble	Soluble
Toluens solubility	Soluble	Soluble
Curing time	24 hrs at 25°C	24 hrs at 25°C
Drying time	2-3 hrs at inside temperature	2-3 hrs at inside temperature
VOC	< 450 g/L	< 350 g/L

### APPLICABLE STANDARDS

**weberdry prime SB** complies with ASTM D 41 Type I or Type II.

### INSTRUCTIONS FOR USE

- The surface must be dry, free from dust, loose or badly adhered particles and any dirt in general, including any pitting or anti-adherent remains.
- weberdry prime SB** can be applied on smooth or rough surfaces. However, it is not advisable to apply the product on very polished surfaces, i.e. burnished or glazed, as these would have to be slightly roughened prior to application.
- Hollows and unevenness must be repaired with cement mortar, to obtain an even surface.

### Application of **weberdry prime SB**

**weberdry prime SB** is supplied ready to use and is cold applied using a brush or roller. It can also be applied with a normal paint spray.

The tools used, including the spray nozzle, must be cleaned with White Spirit type solvent as often as necessary to avoid **weberdry prime SB** from drying on the tools and spoiling them, other than, of course, during any work break, lunch break and at the end of working day.

## COVERAGE RATE

This depends on the smoothness or roughness and porosity of the surface.

Coverage rate around 300 ml/m<sup>2</sup> per coat.

## STORAGE

Maximum One Year in well closed containers and protected against weathering.

## SAFETY PRECAUTIONS

Application should be done in a ventilated area away from any heat source. Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. In case of fire, use CO<sub>2</sub> foam to extinguish. Tightly seal containers when not in use, store them away from heat and carefully dispose empty ones.

## DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.