



weberpremix SRC-1

Ready mixed spatterdash
slurry coat for blocks

*Plastering
Mortars*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
50kg	50kg	50kg	50kg	50kg	50kg	50kg	50kg

PRODUCT

weberpremix SRC-1 is a ready mixed mortar based on mineral bonding agent used for preparing surfaces before the rendering. It improves the adhesion of the new plaster, cement & gypsum based. It is applied on masonry blocks.

Recommended rush-coats according to substrate

SUBSTRATE	PRODUCT
Regular Blocks	weberpremix SRC-1
Light-Weight Blocks	weberpremix SRC-LW
Fair faced Concrete	weberpremix SRC-2
Concrete with SCMs	weberpremix SRC-S

CHARACTERISTICS

Appearance	Grey granular powder
Composition	Portland cement, selected sand, additives
Grain size	0-3mm
Bulk density	1.5 ± 0.1

Wet density	2 ± 0.1
VOC and formaldehyde content ISO/FDIS 11890-2/ GC-MS	None (<10µg/l)
Resistance to fire as per BS EN 998 -1	Class A1

APPLICABLE STANDARDS

BS 5262: 1991
BS 5492: 1990
BS 4551: Part 2: 1998
ASTM C 150
ASTM C 926
ASTM C 897

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrates must be sound, clean, dust free and free from all traces of oil, curing compound, gypsum, paint or laitance. The support must be dampened a few hours before the application of **weberpremix SRC-1**.

PRODUCT PREPARATION

Mix a 50kg bag with 9-11lit of potable cool water in order to obtain the consistency desired.
Mixing has to be done with an electric mixer.

PRODUCT APPLICATION

Apply the **weberpremix SRC-1** using a tyrolean box or a power spray gun.

CURING

Protect the newly applied plaster from sunshine and wind. The new plaster has to be cured with water for at least three days by spraying 3-4 times daily.

CONSUMPTION

Around 4kg/m², depending on the substrate and the application method.

STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

SAFETY PRECAUTIONS

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.