



# weberpremix SRC-S

Ready mixed spatterdash  
slurry coat for very dense  
concrete containing SCMs

*Plastering  
Mortars*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
50kg	50kg	50kg	50kg	50kg	50kg	50kg	50kg

## PRODUCT

**weberpremix SRC-S** is a ready mixed mortar based on mineral bonding agent used for preparing surfaces before the rendering.

It improves the adhesion of the new plaster, cement or gypsum based. It is applied on smooth very dense concrete and concrete containing SCMs (GGBS, Silica fume, Fly ash, Metakaolin...).

### Recommended rush-coats according to substrate

SUBSTRATE	PRODUCT
Regular Blocks	<b>weberpremix SRC-1</b>
Light-Weight Blocks	<b>weberpremix SRC-LW</b>
Fair faced Concrete	<b>weberpremix SRC-2</b>
Concrete with SCMs	<b>weberpremix SRC-S</b>

## CHARACTERISTICS

Appearance	Brownish granular powder
Composition	Portland cement, selected sand, additives, pigments
Grain size	Up to 3mm

VOC	None (<5 g/ LT)
Resistance to fire as per BSEN 998-1	Class A1

## APPLICABLE STANDARDS

BS 5262  
BS 5492  
BS 4551: Part 2  
ASTM C 150  
ASTM C 926  
ASTM C 897

## INSTRUCTIONS FOR USE

### SURFACE PREPARATION

The substrate must be clean, sound, and free from all traces of oil, curing compound, gypsum, paint or laitance. The substrate must be dampened a few hours before the application of **weberpremix SRC-S**.

### PRODUCT PREPARATION

Mix a 50 kg bag with 10 to 12 liters of clean water in order to obtain the consistency desired.

The addition of a bonding agent to **weberpremix SRC-S** is not required. Mixing has to be done with an electric mixer.

### PRODUCT APPLICATION

Apply the **weberpremix SRC-S** using a tyrolean box or a power spray gun.

## CURING

Protect the newly applied plaster from sunshine and wind. The new plaster has to be cured for at least three days by spraying 3 to 4 times daily and, allowed to harden before applying the new plaster.

## CONSUMPTION

Around 4kg/m<sup>2</sup>, depending on the substrate and the application method.

## STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

## SAFETY PRECAUTIONS

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

## DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.