# webertherm movable Profile

## DESCRIPTION

webertherm movable Profile consists of two plastic profiles with an extruded flexible TPE Movement Strip. On both sides of the profile, there are fabric parts welded on by UV method. The Movement Strip is covered with an adhesive Protective Film, which is simply pulled off after the plastering/painting work, for render thicknesses of 3mm or 6mm, toothed, stretchable to 12mm or 20mm. Due to the flexible Movement Strip, the profile can be used on even surfaces as well as in inner/outer corners.

#### **ADDITIONAL ADVANTAGES**

- neat plaster border
- levelled edges
- $\cdot$  easy to install
- enhanced plaster grip due to the grooved profile

# 

# **CHARACTERISTICS**

Items	webertherm movable profile 3mm	webertherm movable profile 6mm
Bar Lengths	200 cm	200 cm
Packed unit	25 bars = 50m	25 bars = 50m
Material	Hard PVC and TPE manufactures in	Hard PVC and TPE manufactures in
	accordance with DIN 16941	accordance with DIN 16941
Fabric width	12.5 cm (each leg)	12.5 cm (each leg)
Mesh size	MW 4x4mm, min. 160g/m2 according to	MW 4x4mm, min. 160g/m2 according to ETAG
	ETAG 004	004
Movement capacity for	stretchabale about 4mm	stretchabale about 4mm
flat surface	compressible about 1-2mm	compressible about 1-2mm
Movement capacity for	stretchabale about 2mm	stretchabale about 2mm
Inner corner	compressible about 1mm	compressible about 1mm

# **SCOPE OF USE**

This profile is used to realize levelled movement joints neat render edges with fine plaster. Can be used for inner/outer corners surfaces, also in drywall construction to equalize small component movements. it can be used as well as Fractioning joints : these joints concern only the rendering system (weber them base and top coat like weberpas deco 350).

### **APPLICATION**

The profile is embedded with mortar adhesive onto the insulation board or into the stud wall joint. After applying the

final rendering remove the protective foil from the TPE movement strip.



#### STORAGE

Cool and dry storage. Horizontal transporting and stocking.

PACKAGING

25 pieces of 2 x 50m each.

