

## Mono component black acrylic based waterproof coating for wet areas

### PRODUCT

**weberdry superblack** is a ready-to-use premium quality acrylic based coating, specially designed for waterproofing in wet areas. When fully cured, **weberdry superblack** forms a durable, elastic, seamless membrane.

### SCOPE OF USE

**weberdry superblack** has been developed for long term waterproofing in the following applications:

- Waterproofing of horizontal surfaces in kitchens
- Wet areas such as bathrooms and showers in residential buildings, hotels & hospitals

### ADVANTAGES

- Easy to apply
- Ready to use
- Tough & elastomeric
- Non-flammable
- Excellent adhesion

### CHARACTERISTICS

Color	Black
Solid content	55% ± 5
Density	1.2 ± 0.1 kg/L
Elongation at break	
ASTM D 412 : 16	>300%
Tensile strength	
ASTM D 412 : 16	>2 Mpa
Water permeability ( 5 bar )	
BS EN 12390-8 : 2009	Nil

### INSTRUCTIONS FOR USE

#### SURFACE PREPARATION

Substrates should be dry, smooth, sound and free from oil, grease, waxes, dust, laitance and all loose matter. Any surface defects should be repaired prior to application of membrane.

#### PRODCUT PREPARATION

Prime the surface with **weberdry superblack** diluted with 10% clean water.

Once primer is dried, apply the first coat of **weberdry super-black**. Allow to dry and then apply the second coat. Wait minimum 6 hours between a coat and another. **weberdry superblack** may be applied by brush or roller.

All corners, cracks or construction joints should receive reinforcement by introducing **weber band** between the first and the second layer.



### CONSUMPTION

The coverage will vary depending on the type of the substrate quality and method of application.

1.2 ± 0.1 kg/m<sup>2</sup>/1 mm WFT

### STORAGE

Can be stored up to one year from manufacturing date, in original packaging, non-open, protected from humidity, hot or freezing temperature.

### SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use,

and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.