

Soil stabilizer

PRODUCT

Soilex 200 is an aqueous, non-ionic stabilized dispersion of carboxylated styrene/butadiene copolymers resistant to saponification.

Soilex 200 is widely used as soil stabilizer. It penetrates into the soil to bind the particles into a more compacted unit, difficult to erode or destabilize.

It can also be added to mortars where a fast development of compressive strength and high flexural strength of mortars are required

SCOPE OF USE

- Stabilizing slopes
- Rail ways
- Roads
- Soil consolidation before excavation

CHARACTERISTICS

Color	Milky white (transparent once applied)
Total Solids content	20 ± 1 % (DIN 53189)
Viscosity	300 mPas (ISO 1652)
Surface Tension	40 mN/m (DIN 53593)
pH	5.5 (DIN 53785)

INSTRUCTIONS FOR USE

PRODUCT APPLICATION

For better dispersion, dilute **Soilex 200** with water at a rate of 15% and use the mix as follows:

First option: Spray on the compacted surface of the soil at a average rate of 1 Lit/m² depending on the soil's type.

Second option: Introduce the material through holes into the soil. 20 mm diameter holes are spread over the area at an average of 1 hole/m² - pour 1 Liter in each hole.

CONSUMPTION

Depends on the soil type, impurities, grading, compaction, weather condition, service age needed..

STORAGE

6 months after manufacturing date in its original packing non open, protected form frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit	20 Lit
200 Lit	200 Lit	200 Lit	200 Lit	200 Lit	200 Lit	200 Lit	200 Lit
drums	drums	drums	drums	drums	drums	drums	drums

by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.