

Silane siloxane acrylic primer

PRODUCT

webercote beton prime is a silane siloxane acrylic based used as a primer coat for **webercote beton plus** after drying it will form a film providing the substrate a homogeneous absorption giving the treated area a uniform aspect.

CHARACTERISTICS

Colors	Grey
pH	8

ADVANTAGES

It protects concrete from water and chloride ions and has the following advantages:

- Water repellency
- Suitable for both new and old concrete

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred.

Before the application of **webercote beton prime**, moisten the substrate and wait until it becomes dry at the surface.

PRODUCT APPLICATION

webercote beton prime is applied using a paint brush or woolen roller. one coat is enough to obtain satisfactory results. It should be dried before the application of the top coat. **webercote beton prime** should be diluted up to 10% before application

CONSUMPTION

0.25-0.45 kg/m².

STORAGE

One year after manufacturing date in its original packing non open, protected from frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The



PACKAGING

Leb	Syria	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	-	20 kg	-

product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of SODAMCO Holding. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.