

Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weberjoint pavement

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SODAMCO S.A.L

Main Road, Hosrayel (Jbeil), P.O. Box 65, Jbeil - Lebanon

T +961 9 790 920/1/2/3

F +961 9 790 924

ATTADAMUNIA for Construction Industries JSC

Tha'labah Al – Ameli Str.-P.O. Box 710844 Amman 11171 Jordan

T +962 6 420 0417

F +962 6 420 0418

SODAMCO Emirates Factory for Building Materials W.L.L.Industrial City of Abu Dhabi

ICAD 3. Plot No. 65 NR29-P.O. Box 96082-Abu-Dhabi -

T +971 2 550 9994

F +971 2 550 9449

SODAMCO S.A.L. - Dubai Branch

Al Quoz Industrial AreaP.O. Box 31320Dubai - U.A.E.

T +971 4 347 2640

F +971 4 340 3420

SODAMCO Qatar W.L.L.

Al Rayan Complex, Bloc B 5th Floor, Flat 17, Rayan Road, Al Musheireb, P.O. Box 22520, Doha – Qatar

T +974 4442 3816 / +974 4442 7651

F +974 4442 5149

SODAMCO Kuwait W.L.L.

Raja Abdulla Al Habbaj Office No. 3F/6, Bloc 7 P.O. Box 496 Salmiya 20005 Kuwait

T +965 2 571 6404 /+965 2 571 0397

F +965 2 571 2721

SODAMCO Muscat L.L.C.

Al Khuwair - Muscat - Sultanate of Oman-P.O. Box 1094 PC 133,

T +968 24 21 83 61

F +968 24 21 83 62

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Office Jeddah)

SODAMCO villa, Prince Mohammad Bin Abdul Aziz Street. P.O. Box 9927, Jeddah 21423 Kingdom of Saudi Arabia

T +966 12 668 3295 +966 12 261 2722

F +966 12 668 1498

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Riyadh Office)

Salahuddin Al Ayoubi Street, Facing Military Airbase Al Bayt 52 Complex, Building 5 Office 1- P.O. Box 1042 Riyadh 11431-Kingdom of Saudi Arabia

T +966 11 473 8751

F +966 11 472 5339

1.4 Emergency telephone number:

UAE:+971 2 550 9994

Lebanon:+9619790920



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

(Contd. of page 1)

Jeddah:+966126683295 Riyadh:+966114738751 Qatar:+97444423816 Jordan: +96264200417 Kuwait:+96525716404 Muscat:+96824218361

Hours of operation: From 8 am to 6 pm

Monday to Friday in Lebanon

Sunday to Thursday in other countries

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement, portland, white calcium diformate

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 3)

(Contd. of page 2)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

The product contains white cement with a content of soluble chromium (VI) below 0.0002% (2ppm),

it doesn't need a reducing agent

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

Determination of endocrine-disrupting properties

Does not contain substances with endocrine-disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:		
CAS: 65997-15-1 EINECS: 266-043-4	cement, portland, white Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	25-50%
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 1317-65-3 EINECS: 215-279-6	calcium carbonate substance with a Community workplace exposure limit	5-10%
CAS: 544-17-2 EINECS: 208-863-7 Reg.nr.: 01-2119486476-24- xxxx	calcium diformate Eye Dam. 1, H318	≥2-<3%

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

The product contains white cement with a content of soluble chromium (VI) below 0.0002% (2 ppm). It doesn't need any chromate reducing agent.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

After eye contact

(Contd. of page 3)

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Rinse mouth. DO NOT induce vomiting. If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** No special measures required.
- 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

EUG



Revision: 08.11.2023 Printing date 08.11.2023 Version number 1

Trade name: weberjoint pavement

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

DNELs		
CAS: 544-	17-2 calcium diformate	
Oral	Derived No Effect Level	23.9 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	4,780 mg/kgxday (worker systemic long term value)
		4,780 mg/kgxday (worker systemic short term value)
		2,390 mg/kgxday (consumer systemic long term value)
		2,390 mg/kgxday (consumer systemic short term value)
	Derived No Effect Level	16.7 mg/cm² (worker local short term value)
		16.7 mg/cm² (worker local long term value)
		8.3 mg/cm² (consumer local long term value)
		8.3 mg/cm² (consumer local short term value)
Inhalative	Derived No Effect Level	337 mg/m³ (worker systemic long term value)
		337 mg/m³ (worker systemic short term value)
		83.2 mg/m³ (consumer systemic long term value)
		83.2 mg/m³ (consumer systemic short term value)
PNECs		
CAS: 544-	17-2 calcium diformate	
Predicted	No-Effect Concentration	1.5 mg/kgxdwt (earth rating factor)
		13.4 mg/kgxdwt (sediment distribution balance)
		1.34 mg/kgxdwt (sea water distribution balance)
Predicted	No-Effect Concentration	2.21 mg/l (earth rating factor)
		0.2 mg/l (sea water rating factor)
		2 mg/l (freeh water reting feater)

Predicted No-Effect Concentration	1.5 mg/kgxdwt (earth rating factor)
	13.4 mg/kgxdwt (sediment distribution balance)
	1.34 mg/kgxdwt (sea water distribution balance)
Predicted No-Effect Concentration	2.21 mg/l (earth rating factor)
	0.2 mg/l (sea water rating factor)
	2 mg/l (fresh water rating factor)
CAS No. / Designation of ma	terial / % / Type / Value / Unit

CAS No. / Designatio	n of material / % / Type / Value / Unit	
CAS: 65997-15-1 cement	, portland, white	
AGW (Germany)	Long-term value: 5 E mg/m³ DFG	
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d	
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4	
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma	
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae	
CAS: 14808-60-7 Silicon	dioxide (Quartz sand)	
BOELV (European Union)	Long-term value: 0.1* mg/m³ *respirable fraction	
MAK (Germany)	Long-term value: 0.05 mg/m³ alveolengängige Fraktion	
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m³ Long-term value: 0.3* 0.1** mg/m³ *total:,**total, respirabel: K	

(Contd. on page 6)



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

			(Contd. of page 5)
	LEP (Spain)	Long-term value: 0.05 mg/m³ *Fracción resp:n,d,y	
	TWA (Italy)	Long-term value: 0.025 mg/m³ A2, (j)	
	VLE (Portugal)	Long-term value: 0.05 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão	
	OEL (Sweden)	Long-term value: 0.1 mg/m³ C, M, respirabel fraktion	
	HTP (Finland)	Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly	
Ī	CAS: 1317-65-3 calciu	um carbonate	
	TWA (Italy)	Long-term value: 10 mg/m³ (e)	

Additional Occupational Exposure Limit Values for possible hazards during processing:

Quartz respirable dust (< 5 µm): 0,15 mg/m³

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection Protective gloves.

Eye/face protection Tightly sealed goggles **Body protection**: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Solid.

Colour: According to product specification

Odour: Uncharacteristic.
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower:
Upper:
Not determined.
Flash point:
Not applicable
Auto-ignition temperature:
Not determined.
Not determined.
Not determined.
Not determined.
Not determined.
Not applicable

(Contd. on page 7)



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

(Contd. of page 6)

Viscosity:

Kinematic viscosity dynamic:Not applicable.

Not applicable.

Solubility

Water: Hardens when in contact with water.

Partition coefficient n-octanol/water (log

value)Not determined.Vapour pressure:Not applicable.

Density and/or relative density

Density:Not applicable.Relative densityNot determined.Vapour densityNot applicable.

Particle characteristics

See section 3.

9.2 Other information

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

Void

Change in condition Softening point/range

Oxidising propertiesNot determined.Evaporation rateNot applicable.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void

SECTION 10: Stability and reactivity

Desensitised explosives

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

(Contd. on page 8)



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

(Contd. of page 7)

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with light alloys in the presence of moisture to form hydrogen

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compor	nents	1	Туре	1	Value	1	Species	
CAS: 65	997-1	5-1 cement,	portland,	white)			
Dermal	LD50	>2,000 mg/	kg (Rabbit))				
CAS: 13	17-65	-3 calcium	carbonate					
Oral	LD50	>5,000 mg/	kg (Rat)					
CAS: 54	4-17-2	calcium d	iformate					
Oral	LD50	2,650 mg/k	g (Rat)					
Dermal	LD50	>2,000 mg/	kg (Rat)					

Skin corrosion/irritation

Causes skin irritation.

CAS: 544-17-2 calcium diformate

Dermal | OECD 404 Acute Dermal Irritation/Corrosion | 0 points (Rabbit Skin - Erytherma/crust)

Serious eye damage/irritation

Causes serious eye damage.

CAS: 544-17-2 d	alcium diforn	nate			
Irritation of eyes	OECD 405 Corrosion	Acute	Eye	Irritation/	1.5 points (rabbit edema of conjunctiva)
					1.7 points (rabbit iris lesion)
					1.9 points (rabbit redenning of conjuntive)
					1.7 points (rabbit turbidity of Horny skin)

Respiratory or skin sensitisation Based on available data, the classification criteria are not met. **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

EUG



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test	Effective concentration / Method / Accessment
	/ Effective concentration / Method / Assessment
CAS: 1317-6	5-3 calcium carbonate
LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))
EC50/48h	>1,000 mg/l (Daphnia magna)
EC50/72h	>200 mg/l (Algae)
CAS: 544-17	-2 calcium diformate
IC50/72h	>1,000 mg/l (Algae)
LC50/96h	<1,000 mg/l (Fish)
LC0/48h	1,000 mg/l (Leuciscus idus (Orfe))
LC0/96h	1,000 mg/l (Fish)
EC50/48h	1,000 mg/l (Daphnia magna)
EC50/72h	570-1,000 mg/l (Algae)
NOEC (72h)	63-500 mg/l (Algae)
NOEC (21d)	100 mg/l (Daphnia magna)
EC 0/48h	250 mg /l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment
CAS: 544-17-2 calcium diformate
EC 50 (3h) >10,000 mg/l (Activated sludge)

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Euro	pean waste catalogue
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 10)



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

(Contd. of page 9)

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.

Thoroughly shake out sacks.

14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 11)



Printing date 08.11.2023 Version number 1 Revision: 08.11.2023

Trade name: weberjoint pavement

(Contd. of page 10)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Classification according to Regulation (EC) No 1272/2008 Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: R&D Department of Weber-Middle East

Contact:

Product Safety T+97125509449

e-mail: DL-weber.productSafety-ME@Saint-gobain.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.