



weberpremix SRC-S (Qatar)

Ready mixed spatterdash slurry coat for very dense concrete containing SCMs

*Plastering
Mortars*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	50kg	-	-	-

PRODUCT

weberpremix SRC-S is a ready mixed mortar based on mineral bonding agent used for preparing surfaces before the rendering. It improves the adhesion of the new plaster, cement or gypsum based. It is applied on smooth very dense concrete and concrete containing SCMs (GGBS, Silica fume, fly ash, Metakaolin...).

ADVANTAGES

- Direct application on smooth substrate: regular blocks and concrete with SCMs.
- Easy and fast application, avoid roughening of concrete.
- Excellent bonding and durability.
- Premix bonding coat requires only additions of water at site.

CHARACTERISTICS

Appearance	Brownish granular powder
Composition	Portland cement, selected sand, additives, pigments
Grain size	0-3mm

Wet density	2 ± 0.1 g/ml
VOC	None (<10µg/l)
Resistance to fire as per BS EN 998 -1	Class A1
Compressive strength as per EN 998-1	≥ 15 MPa
Flexural strength as per EN 998	≥ 3 MPa

APPLICABLE STANDARDS

BS 5262: 1991
BS 5492: 1990
BS 4551: Part 2: 1998
ASTM C 150
ASTM C 926
ASTM C 897

INSTRUCTIONS FOR USE

SURFACE PREPARATION

The substrate must be clean, sound, and free from all traces of oil, curing compound, gypsum, paint or laitance. The substrate must be dampened a few hours before the application of **weberpremix SRC-S**.

PRODUCT PREPARATION

Mix a 50kg bag with 10-12lit of clean water in order to obtain the consistency desired.

The addition of a bonding agent to **weberpremix SRC-S** is not required. Mixing has to be done with an electric mixer.

PRODUCT APPLICATION

Apply the **weberpremix SRC-S** using a tyrolean box or a power spray gun.

CURING

Protect the newly applied plaster from sunshine and wind. The new plaster has to be cured for at least three days by spraying 3-4 times daily and, allowed to harden before applying the new plaster.

CONSUMPTION

Around 4kg/m², depending on the substrate and the application method.

STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

SAFETY PRECAUTIONS

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust.

Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water.

In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.