

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Dry Mortar 300**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SODAMCO S.A.L

Main Road, Hosrayel (Jbeil), P.O. Box 65, Jbeil - Lebanon

T +961 9 790 920/1/2/3

F +961 9 790 924

ATTADAMUNIA for Construction Industries JSC

Tha'labah Al – Ameli Str.-P.O. Box 710844 Amman 11171 Jordan

T +962 6 420 0417

F +962 6 420 0418

SODAMCO Emirates Factory for Building Materials W.L.L.Industrial City of Abu Dhabi

ICAD 3, Plot No. 65 NR29-P.O. Box 96082-Abu-Dhabi -

T +971 2 550 9994

F +971 2 550 9449

SODAMCO S.A.L. - Dubai Branch

Al Quoz Industrial AreaP.O. Box 31320Dubai - U.A.E.

T +971 4 347 2640

F +971 4 340 3420

SODAMCO Qatar W.L.L.

Al Rayan Complex, Bloc B 5th Floor, Flat 17, Rayan Road, Al Musheireb, P.O. Box 22520, Doha – Qatar

T +974 4442 3816 / +974 4442 7651

F +974 4442 5149

SODAMCO Kuwait W.L.L.

Raja Abdulla Al Habbaj Office No. 3F/6, Bloc 7 P.O. Box 496 Salmiya 20005 Kuwait

T +965 2 571 6404 /+965 2 571 0397

F +965 2 571 2721

SODAMCO Muscat L.L.C.

Al Khuwair - Muscat - Sultanate of Oman-P.O. Box 1094 PC 133,

T +968 24 21 83 61

F +968 24 21 83 62

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Office Jeddah)

SODAMCO villa, Prince Mohammad Bin Abdul Aziz Street. P.O. Box 9927, Jeddah 21423 Kingdom of Saudi Arabia

T +966 12 668 3295 +966 12 261 2722

F +966 12 668 1498

SODAMCO Industrial Co. for Construction Chemicals W.L.L (Riyadh Office)

Salahuddin Al Ayoubi Street, Facing Military Airbase Al Bayt 52 Complex, Building 5 Office 1- P.O. Box 1042 Riyadh 11431-Kingdom of Saudi Arabia

(Contd. on page 2)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 1)

T +966 11 473 8751
F +966 11 472 5339

DRYMiX Weber Egypt
5th Industrial Zone, Plot 95B/6, 6th Of October, Egypt
Tel : (+20) 2 3827 4646
Hot line: (+2) 15802

1.4 Emergency telephone number:

UAE:+971 2 550 9994
Lebanon:+9619790920
Jeddah:+966126683295
Riyadh:+966114738751
Qatar:+97444423816
Jordan: +96264200417
Kuwait:+96525716404
Muscat:+96824218361
Egypt: (+20) 2 3827 4646

Hours of operation: From 8 am to 6 pm
Monday to Friday in Lebanon and UAE
Sunday to Thursday in other countries

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05 GHS07

Signal word Danger

(Contd. on page 3)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 2)

Hazard-determining components of labelling:

cement grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

Determination of endocrine-disrupting properties

Does not contain substances with endocrine-disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	50-75%
CAS: 65997-15-1 EINECS: 266-043-4	cement grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203	10-25%
CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 01-2119486795-18-xxxx	calcium carbonate substance with a Community workplace exposure limit	2-5%

SVHC Void

Additional information

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard phrases refer to section 16.

EUG

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 3)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Rinse mouth. DO NOT induce vomiting. If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Not required.

6.2 Environmental precautions: No special measures required.

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep receptacles tightly sealed.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 4)

Ensure good ventilation/exhaustion at the workplace.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs

CAS: 471-34-1 calcium carbonate

Oral	Derived No Effect Level	6.1 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	6.36 mg/m ³ (worker local long term value) 1.06 mg/m ³ (consumer local long term value)

CAS No. / Designation of material / % / Type / Value / Unit

CAS: 14808-60-7 Silicon dioxide (Quartz sand)

BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction
MAK (Germany)	alveolengängige Fraktion
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m ³ Long-term value: 0.3* 0.1** mg/m ³ *total; **total, respirabel: K
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y
TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.025 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitovat raja-arvot, pöly

CAS: 65997-15-1 cement grey

AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 5)

TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae
CAS: 471-34-1 calcium carbonate	
LEP (Spain)	Long-term value: 10 mg/m ³
TWA (Italy)	Long-term value: (10) mg/m ³ (e)
VLE (Portugal)	Long-term value: (10) mg/m ³ (Irritação)

Additional Occupational Exposure Limit Values for possible hazards during processing:

Quartz respirable dust (< 5 µm) : 0,15 mg/m³

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection Protective gloves.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Solid.
Colour:	Grey
Odour:	Uncharacteristic.
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	2,230 °C (DIN, CAS: 14808-60-7 Silicon dioxide (Quartz sand))
Flammability	Product is not flammable.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 6)

Lower and upper explosion limit

Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	Not applicable
Viscosity:	
Kinematic viscosity	Not applicable.
dynamic:	Not applicable.
Solubility	
Water:	Soluble
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not applicable.
Density and/or relative density	
Density:	Not applicable.
Relative density	Not determined.
Vapour density	Not applicable.
Particle characteristics	
See section 3.	

9.2 Other information

Appearance:	
Form:	Powder
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
EU-VOC (g/L)	
Solids content:	100.0 %
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not applicable.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 7)

Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with light alloys in the presence of moisture to form hydrogen

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 65997-15-1 cement grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 471-34-1 calcium carbonate			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

EUG

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test / Effective concentration / Method / Assessment

CAS: 471-34-1 calcium carbonate
--

EC50/72h 14 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment

CAS: 471-34-1 calcium carbonate
--

EC 50 (3h) 1,000 mg/l (microorganisms)
--

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

European waste catalogue

HP4	Irritant - skin irritation and eye damage
-----	---

HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
-----	---

HP13	Sensitising
------	-------------

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.

Thoroughly shake out sacks.

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 9)

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII Entry no. 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 10)

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Department issuing SDS: R&D Department of Weber-Middle East

Contact:

Product Safety
 T+97125509449
 e-mail: DL-weber.productSafety-ME@Saint-gobain.com

Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern (REACH regulation)
- vPvB: very Persistent and very Bioaccumulative

(Contd. on page 12)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 28.03.2024

Version number 1

Revision: 28.03.2024

Trade name: Dry Mortar 300

(Contd. of page 11)

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG