



ACRYCOR M

100% Acrylic Binder, Water Based And Ready To Use
Color Decorative Finish
Façade Render

*Façade and
Thermal Insulation*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	20 kg	-	-	-	-	-	-

PRODUCT

ACRYCOR M is high-quality ready-mixed colored decorative finish façade render, formulated with a 100% acrylic binder. This water-based solution is fortified special aggregates, enhancing its strength and durability. Perfect for exterior applications , .

ACRYCOR M is characterized with its durability, color stability, high resistance against extreme weather conditions, good workability, gives attractive modern architecture, finishing style and available in wide range of uniform colors.

TEXTURES

Fine (400) grading 1.0 mm
Medium coarse (500) grading 1.5 mm
Coarse (600) grading 2 m

ADVANTAGES

- Raw materials are selected according to the highest quality control standards.
- Available in wide range of uniform colors.
- Gives modern decorative finishing style.
- Good workability characteristics.
- The simplicity of usage and application gives very high productivity rates.
- Excellent bonding characteristics.

CHARACTERISTICS

Color	Available in wide range of uniform colors.
Density	Approx. 1.65 Kg/m ³
Solid Content	85-88
pH	7.5 - 9.0
Drying Time	3-4 hours at temperature 20 degrees
Thickness of drying coating layer	1-2 mm per 1 Layer
Base	Acrylic elastomeric polymer and special chemical additives

* the above values may very depending on the supplied color

INSTRUCTIONS FOR USE

SURFACE PREPARATION

- All surfaces should be in a good and strong condition, all substrates should be clean and free from any loose particles, dust, oil, grease, curing agents or paints.
- Any problem in the substrate which may lead to water penetration must be rectified.
- All surfaces should be in a good and strong condition.
- All surfaces should also be clean and free from any loose particles, dust, oil, grease.

PRODUCT PREPARATION

ready to use

PRODUCT APPLICATION

- Concrete painted substrates, cement based plastered walls, block walls, gypsum boards are the suitable substrates to be finished by **ACRYCOR M**
- **ACRYCOR M** can be applied on old and organic paints after surface preparation, making sure no failure of the old paint
- It's advisable to use a suitable sealer such as **DRY SEAL 800 W** or **AL ALMANY** before applying **ACRYCOR M** on surface (according to surface conditions) to avoid salt formation and for uniform surface color by flipping product without any addition or dilution before usage by trowel.
- Scaffolding must be fixed independently to allow for one go application.
- **ACRYCOR M** might be shaken before opening the bag.
- It should be immediately applied on to the well prepared substrate , while it is fresh and workable. In case of delay, do not add additional water. Remix till the material is workable again.
- Apply **ACRYCOR M** to the prepared surface either by conventional hand applied technique using a trowel, or using spraying machine.
- Finish the layer with plastic or wooden trowel before the surface dries in order to reach the required architectural finish.
- To achieve color consistency, apply Acrycor Extra in panels and complete it around the building.
- To ensure color uniformity it is advisable to apply **ACRYCOR M** in the shade, not in direct sun light nor in high wind.
- The work force should be enough to work on large areas, to eliminate cold joints and marks between different applications, it is advisable to apply large areas in one step or split the large areas with grooved lines (Joints).
- As natural raw materials are used for the production of **ACRYCOR M** , it is advisable to apply the entire façade at one time to ensure color uniformity

COVERAGE RATE

Fine (AC400) (2.0-2.5 Kg/m²)

Medium coarse (AC 500) (2.5-2.75 Kg/m²)

Coarse (AC 600) (2.75-3 Kg/m²)

(varies according to surface conditions and the way of application)

STORAGE

Shelf life is 12 months from manufacturing date, in a dry, covered storage area.

SAFETY PRECAUTIONS

While using the product, gloves, mask and goggles should be worn. Splashes to skin or eyes should be washed with clean water, in case of prolonged irritation, seek medical advice.

DISCLAIMER

while the company guarantees its product against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use and

that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

the information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.