



# DRY SEAL PRO

Acrylic Copolymer Emulsion  
Sealer For Porous Substrates

*Façade and  
Thermal Insulation*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
	7.5 Ltr						

## PRODUCT

**SEAL PRO** is a water based sealer manufactured from a selected emulsion polymers, used for sealing porous surfaces prior to applying finishing systems.

**SEAL PRO** specially formulated to provide good impregnation for the surfaces and improve strength of any weak area .

**SEAL PRO** consists of a high performance acrylic copolymer emulsion with fine particle. size to enhance penetration of cementitious substrates.

## USES

**SEAL PRO** can be applied manually by roller/ brush or using spraying machine to increase productivity. It is ideal sealer for indoors.

## ADVANTAGES

- Reduce surface absorption.
- Good bonding and impregnation characteristics to different porous surfaces such as cementitious plaster, cementitious putty, gypsum board, masonry brick, concrete blocks, concrete ...etc.
- Strengthens weak surfaces prior to applying Drymix

- finishing systems
- For indoor use.

## CHARACTERISTICS

Color	white
Recoating time	3 - 4 hours
Final dry	6 hours
Density	1.15 Kg/L

## INSTRUCTIONS FOR USE

### SURFACE PREPARATION

- Cement based walls and screeds should be left to cure for at least 14 days prior to application of **SEAL PRO**.
- All substrates should be clean and free from any loose dust, oil, grease, form-work oil, curing agents, or paint

### PRODUCT PREPARATION

ready to use

### PRODUCT APPLICATION

- Apply **SEAL PRO** using a brush or roller or by spraying on the surface to be sealed, do not dilute.
- Leave the first coat to dry for a minimum of 4 hours prior to applying the second coat.
- Leave the second coat to dry for a minimum of 4 hours prior to applying finishing systems.

## COVERAGE RATE

7-10 m<sup>2</sup>/liter (one coat)  
(Coverage rate may vary depending on surface condition).

## STORAGE

**SEAL PRO** has a high storage stability at 5°C to +35°C. stir always before use.

Shelf life is 12 months from manufacturing date, in original well closed packaging, under shade and in a dry, covered storage area.

## SAFETY PRECAUTIONS

While using the product, gloves, mask and goggles should be worn. Splashes to skin or eyes should be washed with clean water, in case of prolonged irritation, seek medical advice.

## DISCLAIMER

while the company guarantees its product against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

the information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.