

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **webertec grout FG 3 part SG resin**

Safety data sheet no.: 44P2869RB

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedfordshire MK45 5BY

Tel: +44(0)1525 718877

webersds@saint-gobain.com

1.4 Emergency telephone number:

- Ireland: National Poisons Information Centre: +353 (1) 809 2166 (Members of the public 8am - 10pm, 7 days a week) ; +353 (1) 809 2566 (Healthcare professionals only 24/7)

- Iceland: Poisons Information Center - Icelandic University Hospital: +354 543 2222

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Additional information:

EUH208 Contains phthalic anhydride. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32-xxxx	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%
CAS: 85-44-9 EINECS: 201-607-5 Index number: 607-009-00-4	phthalic anhydride ⚠ Resp. Sens. 1, H334; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

SVHC Void

(Contd. on page 3)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 2)

further listed components	
CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4	hydroquinone ⚠ Muta. 2, H341; Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Skin Sens. 1, H317
CAS: 111-42-2 EINECS: 203-868-0 Index number: 603-071-00-1 Reg.nr.: 01-2119488930-28-xxxx	2,2'-iminodiethanol ⚠ STOT RE 2, H373; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315
	??

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin**Additional information** Cool endangered receptacles with water spray.

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Mouth respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

6.2 Environmental precautions:

The product must not get into watercourses
or into the soil.

Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to point 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions: None.

7.3 Specific end use(s)

 No further relevant information available.

EUG

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs

CAS: 100-42-5 styrene

Oral	Derived No Effect Level	0.0077 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	406 mg/kgxday (worker systemic long term value)
		343 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	85 mg/m ³ (worker systemic long term value)
		1 mg/m ³ (consumer systemic long term value)

Ingredients with biological limit values:

CAS: 100-42-5 styrene

VLB (Spain)	400 mg/g creatinina Muestra: orina Momento de Muestero: Final de la jornada laboral Indicador Biológico: Ácido mandélico más ácido fenilglioxílico
	0.2 mg/l Muestra: sangre venosa Momento de Muestero: Final de la jornada laboral Indicador Biológico: Estireno
IBE (Italy)	400 mg/g creatinina Campioni: urine Momento del prelievo: a fine turno Indicatore biologico: acido mandelico + acido fenilgliossilico
	0.2 mg/l Campioni: sangue venoso Momento del prelievo: a fine turno Indicatore biologico: stirene
IBE (Portugal)	400 mg/g creatinina Amostra: urina Momento da amostragem: Fim do turno Indicador biológico: Soma do ácido mandélico e ácido fenilglioxílico
	0.2 mg/L Amostra: sangue venoso Momento da amostragem: Fim do turno Indicador biológico: Estireno
BNO (Finland)	1.2 mmol/l Altiste: virtsan Näytteenottoajankohta: Työpäivän jälkeinen aamu Parametri: MAPGA

(Contd. on page 6)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 5)

CAS No. / Designation of material / % / Type / Value / Unit	
CAS: 100-42-5 styrene	
MAK (Germany)	Long-term value: 86 mg/m ³ , 20 ppm vgl. Abschn. XII
TWA (Italy)	Short-term value: 170 mg/m ³ , 40 ppm Long-term value: 85 mg/m ³ , 20 ppm A4, IBE
VLE (Portugal)	Short-term value: 40 ppm Long-term value: 20 ppm A4; IBE; SCN; irrit. do TRS; neuropatia periférica
HTP (Finland)	Short-term value: 430 mg/m ³ , 100 ppm Long-term value: 86 mg/m ³ , 20 ppm melu

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Hand protection Protective gloves.

Material of gloves

PVA gloves

Neoprene gloves

Nitrile rubber, NBR

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: Amber coloured

Odour: Characteristic

Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling range

145 °C (DIN)

Flammability Not applicable.

Lower and upper explosion limit

Lower: 1.2 Vol % (DIN 51649)

Upper: 8.9 Vol % (DIN 51649)

Flash point: 31 °C (DIN ISO 2592)

Ignition temperature: 480 °C (DIN 51794)

(Contd. on page 7)

-EUG-

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 6)

Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	6 hPa (DIN 51640)
Density and/or relative density	
Density:	Not determined
Relative density	Not determined.
Bulk density:	Not applicable.
Vapour density	Not determined.

9.2 Other information

Appearance:

Form: Liquid

Important information on protection of health and environment, and on safety.

Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Minimum ignition energy
Solvent separation test: Not determined

Solvent content:
Organic solvents: 40.1 %

Change in condition
Softening point/range
Oxidising properties Not determined.

Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives Void

Flammable gases Void

Aerosols Void

Oxidising gases Void

Gases under pressure Void

Flammable liquids

Flammable liquid and vapour.

Flammable solids Void

Self-reactive substances and mixtures Void

Pyrophoric liquids Void

Pyrophoric solids Void

Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable gases in contact with water Void

Oxidising liquids Void

Oxidising solids Void

Organic peroxides Void

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 7)

Corrosive to metals

Void

Desensitised explosives

Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with strong oxidizing agents

Reacts with reducing agents

Reacts with peroxides

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 100-42-5 styrene			
Oral	LD50	>6,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
Inhalative	LC50/4 h	24 mg/l	(Rat)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 8)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Type of test / Effective concentration / Method / Assessment

CAS: 100-42-5 styrene

EC50/48h	4.7 mg/l (Daphnia magna)
EC50/96h	3.32 mg/l (Fish)
EC50/72h	4.9 mg/l (Algae)
NOEC (21d)	1.01 mg/l (Daphnia magna)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

European waste catalogue

HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP10	Toxic for reproduction
HP14	Ecotoxic

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

EUG

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 9)

SECTION 14: Transport information

14.1 UN number or ID number
ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name
ADR
IMDG, IATA

1866 RESIN SOLUTION
RESIN SOLUTION

14.3 Transport hazard class(es)
ADR



Class
Label

3 (F1) Flammable liquids.
3

IMDG, IATA



Class
Label

3 Flammable liquids.
3

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user
Hazard identification number (Kemler code): 30
EMS Number:

Warning: Flammable liquids.
F-E, S-E

14.7 Maritime transport in bulk according to
IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)
Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

Transport category
Tunnel restriction code

3
D/E

UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

EUG

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 10)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

"Control of Substances Hazardous to Health" UK Regulations 2002 (as amended)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 17.03.2022

Trade name webertec grout FG 3 part SG resin

(Contd. of page 11)

H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/eye irritation Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: EHS

Contact:

webersds

+44(0)1525718877

webersds@saint-gobain.com

Version number of previous version: 4

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.