



# weberpas deco 350 (Kuwait)

Acrylic textured coating-  
Sanded finish

*Façade and  
Thermal Insulation*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	25kg	-	-

## PRODUCT

**weberpas deco 350** is a ready to use acrylic sanded finish coating. It includes a special selection of graded quartz sand and fillers that contribute to a unique workability properties while giving an exceptional aesthetic appeal to the product. Special additives improve the product resistance to water and UV lights, thus suitable for external and internal applications.

### CHARACTERISTICS

Colors	The product is available in different colors (white, beige and others)
Paste density	1.84
pH	8
Thickness	2mm
Drying time	24 hours min.
Time to gain mechanical resistance	Not less than 7 days

## INSTRUCTIONS FOR USE

### SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters

and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred.

Prime the substrate with **weberpas PR 300** at least one day before the application of **weberpas deco 350**.

### PRODUCT APPLICATION

**weberpas deco 350** is applied using a stainless steel trowel and leveled with a plastic trowel

### CONSUMPTION

2.5 to 3kg per m<sup>2</sup> depending on site conditions.

### STORAGE

One year after manufacturing date in its original packing non open, protected from frost and heat.

### SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

### DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made

without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### **NOTE**

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.