



weberpas PR 300 ultime color

Acrylic water based primer

*Façade and
Thermal Insulation*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	-	20kg	-

PRODUCT

weberpas PR 300 ultime color is used as a primer coat to provide the substrate with a homogenous absorption giving the treated area a uniform aspect. It is used before the application of **weberpas deco 310, 330, 350** and **355** over cementitious, Gypsum and wood substrates.

CHARACTERISTICS

Colors	The product is available in different colors (white, beige and others)
Paste density	1.25
pH	8

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred.

Before the application of **weberpas PR 300 ultime color**, moisten the substrate and wait until it becomes dry at the surface.

PRODUCT APPLICATION

weberpas PR 300 ultime color is applied using a paint brush or woolen roller. Two coats are usually recommended to obtain satisfactory results applied in crossed layer. The first layer must be dry before the application of the second one. Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water not more than 0.5 liter/20Kg pail may be added.

CONSUMPTION

0.25-0.35 kg/m².

STORAGE

One year after manufacturing date in its original packing non open, protected from frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application

are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.