



weberpas deco 310 ultime color

Acrylic textured coating - Ribbed finish

Façade and Thermal Insulation

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	-	20kg	-

PRODUCT

weberpas deco 310 ultime color is a ready to use acrylic ribbed finish coating. Allowing the use of dark color, **weberpas deco 310 ultime color** is developed with Ultime color technology that reflects infra red radiations, which causes heating, without affecting the color perception. It includes a special selection of graded quartz sand and fillers that contribute to a unique workability properties while giving an exceptional aesthetic appeal to the product. Special additives improve the product resistance to water and UV lights, thus suitable for external and internal applications. **weberpas deco 310 ultime color** is used as well as finishing layer for ETICS/EIFS

CHARACTERISTICS

Colors	The product is available in different colors (wide range of colors)
Paste density	1.80
pH	8
Thickness	2 mm
Drying time	24 hours min.

Time to gain mechanical resistance	7 days min.
SRI values depending on color	
SRI for low wind condition	ASTM E 1980-11: 40 - 56%
SRI for medium wind condition	ASTM E 1980-11: 39 - 55%
SRI for high wind condition	ASTM E 1980-11: 38 - 54%

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred. Prime the substrate with **weberpas PR 300** at least one day before the application of **weberpas deco 310 ultime color**.

PRODUCT APPLICATION

weberpas deco 310 ultime color is applied using a stainless steel trowel and leveled with a plastic trowel giving the directions of the ribs.

CONSUMPTION

3 to 3.5kg per m² depending on substrate conditions

STORAGE

6 months after manufacturing date in its original packing non open, protected from frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.