



weberpas deco 330 ultime color

Plastic decorative coating -
Roll finish

*Facade and
Thermal Insulation*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	-	20kg	-

PRODUCT

weberpas deco 330 ultime color is a ready to use synthetic decorative coating. It is developed with an Ultime color technology that reflects infrared radiation, which causes heating, without affecting or changing the color perception. It includes a special selection of graded fillers that contribute to a unique workability properties while giving an exceptional aesthetic appeal to the product. It is suitable for external and internal applications.

weberpas deco 330 ultime color is used as well as finishing layer for ETICS/EIFS

CHARACTERISTICS	
Colors	The product is available in a wide range of colors
Paste density	1.54
pH	8
SRI values increase by 20 to 60% depending on color	

BENEFITS

- Reflecting Infrared radiation
- Reducing the surface temperature
- No worries of using dark color facade anymore Improve

the facade building durability

- Available on wide range of colors
- Suitable as finishing layer for Facade thermal insulation - EIFS/ETICS

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred.

Prime the substrate with **weberpas PR 300** at least one day before the application of **weberpas deco 330 ultime color**.

PRODUCT APPLICATION

weberpas deco 330 ultime color is applied using a roller.

CONSUMPTION

1.2 kg/m².

STORAGE

One year after manufacturing date in its original packing non open, protected from frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes,

wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.