



weberpremix skim coat fine (KSA)

High quality cementitious rendering

*Plastering
Mortars*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	-	20kg	-

PRODUCT

weberpremix skim coat fine is a high quality pre-blended, cementitious rendering material specifically designed to provide a fair faced finish for rough and uneven substrates. It can be applied on both, Interior and exterior walls and ceilings. **weberpremix skim coat fine** has Superior application and adhesion properties when compared to conventional sand and cement render. It is easy to apply and being pumpable can offer economies in time and labors.

SCOPE OF USE

Ideal for masonry walls and ceilings

- Patching fine surface imperfections such as pinholes and hairline cracks.
- Rendering materials to level defects in concrete walls and ceiling.
- Repairing damage in concrete.

ADVANTAGES

- Easy to use: just add water
- Excellent adhesion to porous substrates
- Sands easily to a smooth finish
- Good workability: does not shrink, crack or sag

- Could be applied on plaster, concrete, with low thickness (up to 1 mm).

CHARACTERISTICS

Appearance	white powder
Bulk density	0.9±0.05
Composition	Synthetic resins, mineral charges and additives
Wet mix life	Around 1 hour at 20°C
Paste density	1.7 ± 0.05
Consumption	1.7 kg/m ² /1mm thickness

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrates must be clean, sound, dust free and free from all traces of oil and laitance. Traces of mould joints must be levelled. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred.

PRODUCT PREPARATION

The **weberpremix skim coat fine** paste is obtained by mixing 20kg bag with 5 to 7 liter of clean cool water using a suitable mixer. Mix up to 3 minutes, to a uniform, lump-free consistency. Avoid over mixing which could entrap air. Once mixed, the working time will depend upon material, ambient and surface conditions.

PRODUCT APPLICATION

weberpremix skim coat fine can be applied between 2-5mm thicknesses in multiple layers. It is applied using a stainless steel trowel. Let sit until almost dry.

- Any cracks should be treated before
- Apply 2 thin layers of the mix using a stainless steel trowel. after fully dry, lightly sand the surface using a sandpaper to remove the marks of trowel
- Additional layers could be applied in order to obtain the desired aspect
- The last layer could be sanded also to remove marks if not desired. Clean tools with water immediately after use. Ideal application temperature is between +5°C and +35°C.

STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands and eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.