



webertherm base profile

Aluminium perforated profile

*Façade and
Thermal Insulation*

PRODUCT DESCRIPTION

Aluminium profile perforated used to align the first row of insulation boards. **webertherm base profile** has a groove in order to evacuate the water from the installed system.

PRODUCT FEATURES

- Good dripping with rain
- Fast and efficient processing
- Clean finish

METHOD OF APPLICATION

Draw a horizontal line at 15cm from the highest point of the ground. For balconies, terraces, stairs, the starting level is set at 1 to 2cm above ground level. In case of insulation / XPS below the ETICS (for waterproofing purpose), you can lay the base profile on top of it. Adjust the position of base profiles using the water level tool, and fix them well with dowels by drilling. The space between 2 dowels should be around 30cm. Moreover, a dowel should be fixed at around 5cm of each edge of the base profile. Keep 2 to 3mm between 2 base profiles. If the substrate is not leveled, use a plastic spacer to adjust the evenness. In case a reinforcement mesh will be embedded in the system, it should be glued on the substrate before fixing **webertherm base profile**. The mesh will be then glued by the **webertherm base** on the board. You can use plastic connector to connect 2 base profiles. **webertherm base profile** could be associated with an edge profile: **webertherm edge profile** 1 wing having a mesh of minimum 10cm width, than will be glued later with the **webertherm base** and the embedded mesh.

PACKAGING

webertherm base profile is 2.5m length and can be available in different width depending on the insulation board thickness.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.