



# weberdry prime WB (UAE)

Water based  
bitumen primer

*Waterproofing*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	140L	-	-	-	-

## PRODUCT

**weberdry prime WB** is a cold applied highly stable bitumen emulsion compound. It contains a high proportion of stabilizers and thickeners to ensure a prolonged shelf life and easy usage. The incorporation of high quality selected bitumen ensures excellent water and moisture proof properties (vapour barrier).

## SCOPE OF USE

- To protect concrete and masonry from attack by sulphates, chlorides and many other moisture and atmospheric borne pollutants.
- weberdry prime WB** is an excellent bituminous primer for use in roofing and fully compatible with most roofing substrates i.e. concrete, Asphalt felt, Asbestos etc. Adjust application rates to suit individual requirements.
- Resists attacks from salts, acids, oil, and alkali.
- weberdry prime WB** is applicable as a primer for bituminous membranes for sub-structures.

## CHARACTERISTICS

Density	Approx 1±0.05kg/lit
Firm set @25°C	24hrs

## APPLICABLE STANDARDS

Complies to ASTM D1227-95 type 3, class I.

## INSTRUCTIONS FOR USE

Above 5°C by brush or roller on clean surface. Brushes should be moistened before use. Wait until first coat has thoroughly dried before applying a second coat. Clean tools with water when wet. If the primer coat is left open for more than 24 hours after it becomes dry, clean the surface of any settled dust and apply first coat of primer.

## COVERAGE

4 to 5m<sup>2</sup>/Lit/Coat, depending on the dry film thickness required.

## STORAGE

Keep away from direct sunlight and store under normal warehouse conditions. Container must be tightly closed. Shelf life of this product is 12 months from the date of manufacturing.

## SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

## DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may

modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

### NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.