



# weberpremix SRC-2 (Qatar)

Ready mixed rush coat for fair faced concrete

*Plastering  
Mortars*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	50kg	-	-	-

## PRODUCT

**weberpremix SRC-2** is a ready mixed mortar based on mineral bonding agent used for preparing surfaces before the rendering. It improves the adhesion of the new plaster, cement & gypsum based. **weberpremix SRC-2** is specially designed to be applied on normal strength fair faced concrete.

## ADVANTAGES

- Direct application on smooth substrate: regular blocks and concrete surface.
- Easy and fast application, avoid roughening of concrete.
- Excellent bonding and durability.
- Premix bonding coat requires only additions of water at site.

## CHARACTERISTICS

Appearance	Grey granular powder
Composition	Portland cement, selected sand, additives
Grain size	0-3mm
Bulk density	1.45±0

Wet density	2±0.1g/ml
VOC	None (<10µg/l)
Resistance to fire as per BS EN 998 -1	Class A1
Compressive strength as per EN 998	≥15MPa
Flexural strength as per EN 998	≥2MPa

## APPLICABLE STANDARDS

BS 5262: 1991  
BS 5492: 1990  
BS 4551: Part 2: 1998  
ASTM C 150  
ASTM C 926  
ASTM C 897

## INSTRUCTIONS FOR USE

### SURFACE PREPARATION

The substrates must be sound, clean, dust free and free from all traces of oil, curing compound, gypsum, paint or laitance. The support must be dampened a few hours before the application of **weberpremix SRC-2**.

### PRODUCT PREPARATION

Mix a 50kg bag with 9.75-11.75lit of clean water in order to obtain the consistency desired. Mixing has to be done with an electric mixer.

## PRODUCT APPLICATION

Apply the **weberpremix SRC-2** using a tyrolean box or a power spray gun.

Ideal application temperature is between +5°C to +35°C. If the temperature is higher than 35°C, make sure to use cool water when mixing to keep the mixed material below 30°C.

## CURING

Protect the newly applied plaster from sunshine and wind. The new plaster has to be cured with water for at least three days by spraying 3-4 times daily.

## CONSUMPTION

Around 4kg/m<sup>2</sup>, depending on the substrate and the application method.

## STORAGE

12 months after manufacturing date in original and non-open packaging, under cover, in dry condition, away from humidity, protected from extreme temperatures and direct sunlight.

## SAFETY PRECAUTIONS

The product contains cement powders which, when mixed with water, release alkalis that could be harmful to the skin. It is preferable that the application be done in a ventilated area, and to wear protective gear for hands, eyes and respiratory system and to avoid breathing of the dust. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention. The product is non-flammable.

## DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

## NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (previously SODAMCO Holding). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.