



DRY SEAL 800 W

High Quality Polymer Emulsion Sealer For Porous Substrates

Façade and Thermal Insulation

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	125 Kg	-	-	-	-	-	-
-	12.5 Kg	-	-	-	-	-	-

PRODUCT

DRY SEAL 800 W is a high quality aqueous dispersion sealer manufactured from selected emulsion polymers.

DRY SEAL 800 W is to be used for sealing porous surfaces prior to applying **Drymix weber** finishing systems such as **DRY DÉCOR ACRYCOR** systems.

DRY SEAL 800 W is specially formulated to provide good impregnation of substrates and improve strength of weak substrates.

DRY SEAL 800 W can be applied manually by roller/ brush or using spraying machine to increase productivity.

DRY SEAL 800 W is ideal sealer for indoors and outdoors location.

ADVANTAGES

- Reduces surface salt and efflorescence.

- Reduce surface absorption.
- Excellent bonding and impregnation characteristics to different porous surfaces such as cementitious plaster, cementitious putty, gypsum board, masonry brick, concrete blocks, concrete ...etc.
- Strengthens weak surfaces prior to applying Drymix finishing.

CHARACTERISTICS	
Color	Milky white.
pH	8±0.5
Density	Around 1.3kg/liter
Solid content	<30 (by volume percentage)

INSTRUCTIONS FOR USE

SURFACE PREPARATION

Cement based walls should be left to cure for at least 14 days prior to applying **DRY SEAL 800 W**.

All substrates must be clean and free from any loose dust, oil, grease, form-work oil, curing agents, or paint.

PRODUCT PREPARATION

Ready to use.

PRODUCT APPLICATION

Apply **DRY SEAL 800 W** using a brush or roller or by spraying on the surface to be sealed, do not dilute.

Leave the first coat to dry for a minimum of 4 hours prior to applying the second coat of sealer.

Leave the second coat to dry for a minimum of 4 hours prior to applying **Drymix weber** finishing systems.

COVERAGE RATE

7-8m²/liter per 1 coat.

(Coverage rate may vary depending on surface condition).

STORAGE

DRY SEAL 800 W has a high storage stability at 5°C to +35°C. Stir always before use.

Shelf life is 12 months from manufacturing date, in original well closed packaging, under shade and in a dry, covered storage area.

SAFETY PRECAUTIONS

While using the product, gloves, mask and goggles should be worn. Splashes to skin or eyes should be washed with clean water, in case of prolonged irritation, seek medical advice.

DISCLAIMER

While the company guarantees its product against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.