



weberpas deco 340 (Lebanon)

Highly elastic facade coating

*Facade and
Thermal Insulation*

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
18kg	-	-	-	-	-	-	-

PRODUCT

weberpas deco 340 is a ready to use one component product, based on an elastomeric acrylic aqueous dispersion containing pigments, mineral fillers and rheological additives. It can be used on properly prepared surfaces such as concrete, masonry and Exterior Insulated and Finish Systems (EIFS). It is possible to over-coat existing coatings on a mineral or synthetic resin base that are well adhered and in good condition.

weberpas deco 340 forms a protective and decorative film with permanent elasticity and excellent adhesion.

weberpas deco 340 shows an exceptional resistance to extreme weather conditions. It is non-toxic and environmental friendly.

CHARACTERISTICS

Colors	The product is available in different colors (white, beige and others)
Paste density	1.150
Elongation at break	~400%
Thickness	Max. 2mm in different layers

Time to waterproof of weberpas deco 340	Not less than 7 days
Time to get gain final resistance of weberpas deco 340	Not less than 7 days
Drying time	48 hours min.
Time between coats of weberpas deco 340	6 to 8 hours

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

Substrate must be clean, sound and free from greasy matters and dust. Remove all traces of paint, mould oil which may affect the adhesion. Before the application the substrate must be sufficiently cured in a way that any shrinkage has already occurred. All imperfections, cracks must be repaired using suitable materials from our range of products before application of **weberpas deco 340**

PRODUCT APPLICATION

Stir thoroughly before and during use. **weberpas deco 340** is applied using a cotton roll. Two coats are usually required to obtain satisfactory results but additional coats can be used if required. On smooth concrete, prime the substrate with **weberpas PR 339** at least one day before application of **weberpas deco 340**.

First coat to be diluted with 25 % of clean water. A second coat to be applied with 10% dilution. Third coat can be applied if necessary.

CONSUMPTION

0.3 to 0.7kg/m²/coat using a cotton roll, depending on the type of substrate and way of usage.

STORAGE

One year after manufacturing date in its original packing non open, protected from frost and heat.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting. In both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.