



weberdry prime WB (Kuwait)

Cold applied bitumen
coating

Waterproofing

Leb	Egypt	Jordan	UAE	Qatar	Kuwait	KSA	Oman
-	-	-	-	-	20L	-	-

- Exterior of shear walls that will be buried underground.
- Under tiles in bathroom and kitchen areas or under roof tiles due to its exceptional resistance to water.

PRODUCT

weberdry prime WB is water base cold applied stable bitumen emulsion that dries to give a flexible, joint less, waterproof coating.

weberdry prime WB acts as a damp-proof membrane and vapour seal for concrete and masonry. It can also be used as a protective coating for concrete below ground.

PROPERTIES/ADVANTAGES

- Easy to apply.
- Economical in use.
- Adhere to wide range of materials such as steel and concrete.
- Resistance to water, most salt solutions and to some acid & alkali solutions.

SCOPE OF USE

- **weberdry prime WB** is an excellent bituminous primer for use in roofing and fully compatible with most roofing substrates i.e. concrete, Asphalt felt, Asbestos etc. Adjust application rates to suit individual requirements.
- It provides after drying an effective primer coat prior to application of waterproofing membranes and liquid applied protective coatings containing bitumen.

weberdry prime WB can also be used:

- Exterior of underground water tanks and pipelines.

CHARACTERISTICS

Color	Dark brown
Specific gravity @25°C	1±0.02kg/liter ±0.05
Solid content	30%±2%
Application temperature	5°C to +40°C
Fire resistance (wet)	Non flammable
Firm set	1 day

APPLICABLE STANDARDS

Conforms to ASTM D-1227 Type III Class 1

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

All surfaces to which **weberdry prime WB** is applied must be sound, stable with an even finish and free from dirt, dust, loose debris, grease, cracks and holes must be repaired before application.

PRODUCT APPLICATION

weberdry prime WB may be applied by brush, or roller. Ensure the contents of the containers are well mixed before application.

It is recommended that two or more coats must be applied to ensure a durable finish (depending on the condition of the substrate).

Do not apply **weberdry prime WB** to external areas in wet weather or when rain is expected. Apply the 1st coat by a brush, roller or squeegee. Typically the coating applied @1.1lt./m² will give a Dry Film Thickness of 550 microns. The second coat is to be applied at the same rate and at right angles to the first coat. The first coat must be dry before applying the second coat. However, the coverage depends on the smoothness and porosity of the substrate and the required thickness of the coating.

CONSUMPTION

Coverage and number of coats depend on the surface porosity. Depending on the dry film thickness required, apply the dry bitumen at approx. 1.1lt./m².

EQUIPMENT CLEANING

weberdry prime WB may be removed from tools and equipment with water when it is wet. On drying, it may be removed using solvent.

STORAGE

weberdry prime WB has a shelf life of 12 months when stored under cover, out of direct sunlight and protect from extreme temperatures. In tropical climates the product must be stored in an air conditioned environment. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

SAFETY PRECAUTIONS

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting; in both cases seek medical attention. The product is non-flammable.

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Saint-Gobain Middle East Holding SAL (Previously SODAMCO Holding SAL). The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.